

INDUSTRIAL COMPONENT DATA

GLC0400C1UL LOVATO Tripolar Switch Bottom Cabinet 400A AC21A C1 UL1008

Brand: LOVATO ELECTRIC | Manufacturer Part Number: GLC0400C1UL



Manufacturer	LOVATO ELECTRIC
MPN / Reference	GLC0400C1UL
Catalog number	10000
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-DAFBADA21F
Generated	2026-08-03

Product Overview

Tripolar Switch Bottom Cabinet 400A AC21A C1 UL1008

Three-pole changeover switch, UL1008, 400A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Switch disconnectors - LOVATO ELECTRIC

Additional Product Information

GLC0400C1UL

Three-pole changeover switch, UL1008, 400A

Technical specifications

Type of product:Changeover switchesNumber of poles:3Type of operating voltage:ACIEC Conventional free air thermal current Ith [A]:400UL Standard:UL1008Type of installation:Screw on plateOrder code GLC0400C1UL

Weight [g] 7740

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 330X270X240

Volume [cm³] 21384

Bar code [EAN13] 8013975267158

HS Code 85365080

1257.58 £

ETIM for GLC0400C1UL Low-voltage industrial controls and switchgear (EC000216)

Feature Name	
Feature Value	
Device construction (EF008240)	
Built-in device fixed built-in technique	
Type of control element (EF006976)	
Door coupling rotary drive	
Type of electrical connection of main circuit (EF006819)	
Bolt connection	
Rated operating voltage (EF001435)	
400 V	
Version as reversing switch (EF009408)	
No	
Voltage release optional (EF007491)	
No	
Motor drive optional (EF007386)	
No	
Suitable for distribution board installation (EF007262)	
No	
Suitable for front mounting 4-hole (EF007247)	
No	
Version as maintenance-/service switch (EF006986)	
Yes	
Version as safety switch (EF006985)	
No	
Version as main switch (EF006981)	
Yes	
Version as emergency stop installation (EF006959)	
No	
Motor drive integrated (EF006697)	
No	
Interlockable (EF006281)	
No	
Max. rated operation voltage Ue AC (EF007355)	
600 V	
Rated short-time withstand current Icw (EF007050)	
12.5 kA	
Rated operation power at AC-23, 400 V (EF007027)	
200 kW	
Number of auxiliary contacts as ch...	

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / GLC0400C1UL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.