

INDUSTRIAL COMPONENT DATA

GLZM0250 LOVATO 3P SWITCH 250A-MET ENCL-R/Y
HANDLE

Brand: LOVATO ELECTRIC | Manufacturer Part Number: GLZM0250



Manufacturer	LOVATO ELECTRIC
MPN / Reference	GLZM0250
Catalog number	10000
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-D8F61D6AB4
Generated	2026-08-04

Product Overview

3P SWITCH 250A-MET ENCL-R/Y HANDLE

Three-pole switch disconnecter in IEC/EN IP65 metal enclosure. With rotating red/yellow handle, 250A. Enclosure dimensions: 300x400x250mm/11.8x15.8x9.8"

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Switch disconnectors - LOVATO ELECTRIC

Additional Product Information

GLZM0250

Three-pole switch disconnecter in IEC/EN IP65 metal enclosure. With rotating red/yellow handle, 250A. Enclosure dimensions: 300x400x250mm/11.8x15.8x9.8"

Technical specifications

Type of product: Switch disconnectors
Number of poles: 3
Type of enclosure: Metallic enclosure - Red/Yellow handle
Type of operating voltage: AC
IEC Conventional free air thermal current I_{th} [A]: 250
Type of installation: Enclosed
Order code

GLZM0250

Weight [g] 8080

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 330X410X320

Volume [cm³] 43296

Bar code [EAN13] 8013975235690

HS Code 85365080

ETIM for GLZM0250 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Device construction (EF008240)

Complete device in housing

Colour control element (EF007167)

Red

Type of electrical connection of main circuit (EF006819)

Bolt connection

Degree of protection (IP), front side (EF003118)

IP65

Rated operating voltage (EF001435)

400 V

Version as reversing switch (EF009408)

No

Voltage release optional (EF007491)

No

Motor drive optional (EF007386)

No

Suitable for distribution board installation (EF007262)

No

Suitable for front mounting 4-hole (EF007247)

No

Version as maintenance-/service switch (EF006986)

Yes

Version as safety switch (EF006985)

No

Version as main switch (EF006981)

Yes

Version as emergency stop installation (EF006959)

Yes

Motor drive integrated (EF006697)

No

Interlockable (EF006281)

Yes

Rated permanent current at AC-23, 400 V (EF011777)

250 A....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / GLZM0250 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.