

INDUSTRIAL COMPONENT DATA

GMFJ060C12 LOVATO 3P SWITCH DISC. W/FUSE HOLDER J 60A C12

Brand: LOVATO ELECTRIC | Manufacturer Part Number: GMFJ060C12



Manufacturer	LOVATO ELECTRIC
MPN / Reference	GMFJ060C12
Catalog number	10000
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-B4A08BC31B
Generated	2026-08-04

Product Overview

3P SWITCH DISC. W/FUSE HOLDER J 60A C12

Three-pole disconnect switch with fuse holder (UL98). 60A. J UL fuse type. Central command pole

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Switch disconnectors - LOVATO ELECTRIC

Additional Product Information

GMFJ060C12

Three-pole disconnect switch with fuse holder (UL98). 60A. J UL fuse type. Central command pole

Technical specifications

Type of product: Switch disconnectors with fuse holder
Number of poles: 3
Type of operating voltage: AC
IEC Conventional free air thermal current I_{th} [A]: 63
UL Standard: UL98
Type of fuse: J
Type of installation: Screw on plate
Order code GMFJ060C12

Weight [g] 1528

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 210X145X135

Volume [cm³] 4110.75

Bar code [EAN13] 8013975229736

HS Code 85365080

509.99 £

ETIM for GMFJ060C12 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Device construction (EF008240)

Built-in device fixed built-in technique

Type of control element (EF006976)

Door coupling rotary drive

Type of electrical connection of main circuit (EF006819)

Frame clamp

Degree of protection (IP), front side (EF003118)

IP20

Rated operating voltage (EF001435)

400 V

Version as reversing switch (EF009408)

No

Voltage release optional (EF007491)

No

Motor drive optional (EF007386)

No

Suitable for distribution board installation (EF007262)

No

Suitable for front mounting 4-hole (EF007247)

No

Interlockable (EF006281)

No

Rated permanent current at AC-23, 400 V (EF011777)

63 A

Rated permanent current at AC-21, 400 V (EF009165)

63 A

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated short-time withstand current Icw (EF007050)

2.5 kA

Rated operation power at AC-23, 400 V (EF007027)

30 kW

Number of auxil...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / GMFJ060C12 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.