

INDUSTRIAL COMPONENT DATA

GX1608P25 LOVATO ON-OFF SW. 4P 16A PLAST. ENCL. 90X90 R/Y

Brand: LOVATO ELECTRIC | Manufacturer Part Number: GX1608P25



Manufacturer	LOVATO ELECTRIC
MPN / Reference	GX1608P25
Catalog number	10000
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-9088B035F5
Generated	2026-08-05

Product Overview

ON-OFF SW. 4P 16A PLAST. ENCL. 90X90 R/Y

Enclosed rotary cam switch GX series, ON-OFF switch 4 poles 16A in plastic enclosure 90X90mm with red/yellow handle

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Rotary cam switches - LOVATO ELECTRIC

Additional Product Information

GX1608P25

Enclosed rotary cam switch GX series, ON-OFF switch 4 poles 16A in plastic enclosure 90X90mm with red/yellow handle

Technical specifications

Type of product:ON/OFF switchesSwitching diagram:08 - ON/OFF switch 4 polesIEC Conventional free air thermal current

Ith [A]:16Mounting form:P25 - Plastic enclosure with red/yellow handleSeries:GX - square-shaped contact blockOrder code

GX1608P25

Weight [g] 345

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm]

Volume [cm³] 0

Bar code [EAN13] 3850144161856

HS Code 85365080

ETIM for GX1608P25 Low-voltage industrial controls and switchgear (EC001105)

Feature Name
Feature Value
Type of control element (EF006976)
Short thumb-grip
Type of electrical connection of main circuit (EF006819)
Screw connection
Degree of protection (IP), front side (EF003118)
IP65
Housing material (EF001596)
Plastic
Model (EF000010)
On/Off switch
Complete device in housing (EF007317)
Yes
Suitable for intermediate mounting (EF007264)
No
Suitable for distribution board installation (EF007262)
Yes
Suitable for front mounting (EF007246)
No
Suitable for floor mounting (EF007243)
No
With retraction in 0-position (EF002428)
No
With zero (off) position (EF001416)
Yes
Number of poles (EF001391)
4
Rated permanent current I_u (EF001389)
16 A
Rated operation power at AC-3, 400 V (EF001364)
4.5 kW

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / GX1608P25 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.