

INDUSTRIAL COMPONENT DATA

GX2054U47 LOVATO C/O W/O 0 1P 20A SNAP FRNT MNT D22 48X48

Brand: LOVATO ELECTRIC | Manufacturer Part Number: GX2054U47



Manufacturer	LOVATO ELECTRIC
MPN / Reference	GX2054U47
Catalog number	10000
Category	Selector switch, complete
Minimum order	1 Pcs
Document ID	EO-CCE1782A6C
Generated	2026-08-06

Product Overview

C/O W/O 0 1P 20A SNAP FRNT MNT D22 48X48

ROTARY CAM SWITCH GX SERIES, CHANGEOVER SWITCH WITHOUT 0 1 POLE 20A, FOR SNAP ON FRONT MOUNTING WITH BLACK HANDLE FOR HOLE DIAM. 22MM FINXING, FRONT PLATE 48X48MM

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **LOVATO ELECTRIC > Rotary cam switches - LOVATO ELECTRIC**

Additional Product Information

Order code GX2054U47

Weight [g] 116

Qty. per package

Multiple qty. of packs per order

Package dimensions [mm] 070X050X100

Volume [cm³] 350

Bar code [EAN13] 8013975191286

HS Code 85365080

Dimensions

Wiring diagram

Certifications:

cULus

EAC Compliance:

IEC/EN/BS 60947-1

IEC/EN/BS 60947-3

IEC/EN/BS 60947-5-1

IEC/EN/BS 61058-1

UL60947-4-1

CSA C22.2 n° 14 Product designation Rotary cam switches

Product type designation GX20

General characteristics

Switching diagram 54 - Changeover switch without 0 1 pole

N° of elements 1

Mounting form Snap on front mounting with black handle for hole diam. 22mm finxing (U47)

Contact characteristics

Rated insulation voltage U_i

IEC/EN V 690

UL/CSA V 600

Rated impulse withstand voltage U_{imp} kV 6

Conventional free air thermal current I_{th}

IEC/EN A 20

UL/CSA A 15

Rated operational voltage V 440

Rated operational impulse voltage kV 4

Maximum fuse size for short-circuit protection I_n (gG)

10kA A 20

15kA A 20

25kA A 20

Rated short time current I_{cw}

1s A 250

Conductivity 10/5 mA/V

Operational current I_e IEC/EN

AC1/AC21A

A 20

AC15

110V A 10

220/230V A 8

380/400V A 6

660/690V A 1.5

Rated operational power in AC

Three-phase AC3

220/230V kW 3.7

380/440V kW 5.5

500/690V kW 5.5

Single-phase AC3

110V kW 0.75

220/230V kW 1.8

380/440V kW 3

Three-phase AC23A

220/230V kW 4

380/440V kW 7.5
500/690V kW 7.5
Single-phase AC23A
110V kW 0.75
220/230V kW 2.2
380/440V kW 3.5
Rated operational current in DC
DC21A
48V A 20
60V A 20
110V A 4
220V A 0.6
440V A 0.25
DC23A (poles in...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / GX2054U47 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.