

INDUSTRIAL COMPONENT DATA

GX3251O LOVATO CHANGEOVER SW. 1P 32A REAR MOUNT. 65x65

Brand: LOVATO ELECTRIC | Manufacturer Part Number: GX3251O



Manufacturer	LOVATO ELECTRIC
MPN / Reference	GX3251O
Catalog number	10000
Category	Selector switch, complete
Minimum order	1 Pcs
Document ID	EO-DD36288486
Generated	2026-08-05

Product Overview

CHANGEOVER SW. 1P 32A REAR MOUNT. 65x65

ROTARY CAM SWITCH GX SERIES, CHANGEOVER SWITCH 1 POLE 32A, FOR REAR MOUNTING WITH BLACK HANDLE, FRONT PLATE 65X65MM

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **LOVATO ELECTRIC > Rotary cam switches - LOVATO ELECTRIC**

Additional Product Information

Order code GX3251O

Weight [g] 310

Qty. per package

Multiple qty. of packs per order

Package dimensions [mm] 071X083X108

Volume [cm³] 636.444

Bar code [EAN13] 8013975217573

HS Code 85365080

Dimensions

Wiring diagram

Certifications:

cULus

EAC Compliance:

IEC/EN/BS 60947-1
IEC/EN/BS 60947-3
IEC/EN/BS 60947-5-1
IEC/EN/BS 61058-1
UL60947-4-1
CSA C22.2 n° 14 Product designation Rotary cam switches
Product type designation GX32
General characteristics
Switching diagram 51 - Changeover switch 1 pole
N° of elements 1
Mounting form Rear mounting with black handle (O)
Contact characteristics
Rated insulation voltage U_i
IEC/EN V 690
UL/CSA V 600
Rated impulse withstand voltage U_{imp} kV 6
Conventional free air thermal current I_{th}
IEC/EN A 32
UL/CSA A 32
Rated operational voltage V 440
Rated operational impulse voltage kV 4
Maximum fuse size for short-circuit protection I_n (gG)
10kA A 35
15kA A 35
25kA A 35
Rated short time current I_{cw}
1s A 1000
Conductivity 10/5 mA/V
Operational current I_e IEC/EN
AC1/AC21A
A 32
AC15
110V A 25
220/230V A 20
380/400V A 10
660/690V A 2
Rated operational power in AC
Three-phase AC3
220/230V kW 7.5
380/440V kW 11
500/690V kW 11
Single-phase AC3
110V kW 1.8
220/230V kW 3.5
380/440V kW 5.5
Three-phase AC23A
220/230V kW 8

380/440V kW 15
500/690V kW 15
Single-phase AC23A
110V kW 2.2
220/230V kW 3.5
380/440V kW 6
Rated operational current in DC
DC21A
48V A 32
60V A 32
110V A 5
220V A 0.8
440V A 0.25
DC23A (poles in series)
24V A 32 (1)
48V A 32 (2)
60V A 32 (3)
110...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / GX3251O with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.