

INDUSTRIAL COMPONENT DATA

KMP2L03 LOVATO LIMIT SWITCH, K SERIES, HINGE OPERATING, 1 BOTTOM CABLE ENTRY. DIMENSIONS TO EN 50047, METAL ..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: KMP2L03



Manufacturer	LOVATO ELECTRIC
MPN / Reference	KMP2L03
Catalog number	10000
Category	End switch
Minimum order	1 Pcs
Document ID	EO-114DD1D26C
Generated	2026-08-05

Product Overview

LIMIT SWITCH, K SERIES, HINGE OPERATING, 1 BOTTOM CABLE ENTRY. DIMENSIONS TO EN 50047, METAL BODY, CONTACTS 3NC SLOW BREAK. LONG SOLID SHAFT

HINGE LONG SHAFT METAL SAFETY SWITCH 3NC

Limit switch, K series, hinge operating, 1 bottom cable entry. Dimensions to EN 50047, metal body, contacts 3NC slow action. Long solid shaft

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LOVATO ELECTRIC > Limit, micro and foot switches - LOVATO ELECTRIC
--------------	--

Additional Product Information

KMP2L03

Limit switch, K series, hinge operating, 1 bottom cable entry. Dimensions to EN 50047, metal body, contacts 3NC slow action. Long solid shaft

Technical specifications

Type of product:Safety limit switchesProduct characteristics:Hinge operatingHousing material:Aluminium-zinc alloyRod characteristics:Long solidCable entry:M20 on the bottomType of contacts:3NC Slow actionOrder code KMP2L03

Weight [g] 254

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 185X041X085

Volume [cm³] 644.725

Bar code [EAN13] 8013975143391

HS Code 85365080

101.25 £

ETIM for KMP2L03 Sensors (EC000030)

Feature Name

Feature Value

Alignment of the control element (EF008793)

Other

Type of interface (EF006977)

None

Type of control element (EF006976)

Other

Degree of protection (IP) (EF005474)

IP65

Construction type housing (EF004008)

Cuboid

Explosion safety category for dust (EF003998)

None

Explosion safety category for gas (EF003997)

None

Type of electric connection (EF003961)

Cable entry metrical

Type of interface for safety communication (EF003956)

None

Coating housing (EF001601)

Powder coated

Housing material (EF001596)

Metal

Switching function (EF000189)

Slow-action switch

Ambient temperature during operating (EF007515)

-25 °C

Switching function latching (EF007447)

No

Output electronic (EF006987)

No

Forced opening (EF006694)

Yes

With status indication (EF001602)

No

Suitable for safety functions (EF001597)

Yes

Number of contacts as change-over contact (EF008257)

0

Numb...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / KMP2L03 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.