

INDUSTRIAL COMPONENT DATA

M0P009121206010 LOVATO DIRECT-ON-LINE-STARTER, ENCLOSED WITH THERMAL OVERLOAD RELAY, WITH START AND STOP/RES..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: M0P009121206010



Manufacturer	LOVATO ELECTRIC
MPN / Reference	M0P009121206010
Catalog number	009121206010
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-E228A3933A
Generated	2026-08-02

Product Overview

DIRECT-ON-LINE-STARTER, ENCLOSED WITH THERMAL OVERLOAD RELAY, WITH START AND STOP/RESET BUTTONS, WITH BG09/BG12 CONTACTOR, 10A MAX (3...4KW AT 400V), IP65. CONTACTOR COIL VOLTAGE 120VAC 60HZ

DOL STARTER M0P 120/60 6-10A

Direct-on-line-starter, 6...10A (3...4kW at 400V), IP65, contactor coil voltage 120VAC 60Hz, non-metallic enclosure, with thermal overload relay, with START and STOP/RESET buttons

DIRECT STARTER, 6...10A (3...4KW AT 400V), CONTACTOR COIL VOLTAGE 120VAC 60HZ, WITH THERMAL RELAY IN IP65 INSULATED ENCLOSURE, WITH START AND STOP/RESET BUTTONS,

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LOVATO ELECTRIC > Electromechanical starters - LOVATO ELECTRIC
--------------	--

Additional Product Information

M0P009121206010

Direct-on-line-starter, 6...10A (3...4kW at 400V), IP65, contactor coil voltage 120VAC 60Hz, non-metallic enclosure, with thermal overload relay, with START and STOP/RESET buttons

Technical specifications

Type of product:Direct-on-line-startersIEC operating current and power Ie (AC3) 400V [A/Kw]:10A / 4kWUL/CSA

horsepower ratings 480V [HP]:5Type:Enclosed with thermal overload relayType of coil:AC coilType of pushbutton:With

Start-Stop/Reset buttons Contactor coil voltage: 120VAC 60HZ Order code M0P009121206010

Weight [g] 760

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 187X092X160

Volume [cm³] 2752.64

Bar code [EAN13] 8013975155691

HS Code 85371098

203.77 £

ETIM for M0P009121206010 Low-voltage industrial controls and switchgear (EC001037)

Feature Name

Feature Value

Degree of protection (NEMA) (EF011959)

4X

Type of motor starter (EF009598)

Direct starter

Voltage type for actuating (EF008242)

AC

Type of electrical connection for auxiliary- and control current circuit (EF006979)

Screw connection

Type of electrical connection of main circuit (EF006819)

Screw connection

Release class (EF006668)

CLASS 10 A

Degree of protection (IP) (EF005474)

IP65

Rated control supply voltage AC 60 Hz (EF003979)

120 V

Overload release current setting (EF002336)

6 A

Temperature compensated overload protection (EF009604)

Yes

Supporting protocol for SafetyBUS p (EF007527)

No

Supporting protocol for PROFIsafe (EF007526)

No

Supporting protocol for PROFINET....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / M0P009121206010 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.