

## INDUSTRIAL COMPONENT DATA

# M0P00912460605 LOVATO DIRECT-ON-LINE-STARTER, ENCLOSED WITH THERMAL OVERLOAD RELAY, WITH START AND STOP/RESE..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: M0P00912460605



|                 |                                         |
|-----------------|-----------------------------------------|
| Manufacturer    | LOVATO ELECTRIC                         |
| MPN / Reference | M0P00912460605                          |
| Catalog number  | 00912460605                             |
| Category        | Motor starter/Motor starter combination |
| Minimum order   | 1 Pcs                                   |
| Document ID     | EO-8DA5CC3FE8                           |
| Generated       | 2026-08-02                              |

## Product Overview

DIRECT-ON-LINE-STARTER, ENCLOSED WITH THERMAL OVERLOAD RELAY, WITH START AND STOP/RESET BUTTONS, WITH BG09/BG12 CONTACTOR, 5A MAX (1.5...2.2KW AT 400V), IP65. CONTACTOR COIL VOLTAGE 460VAC 60HZ

DOL STARTER M0P009 460/60 3-5A

Direct-on-line-starter, 3...5A (1.5...2.2kW at 400V), IP65, contactor coil voltage 460VAC 60Hz, non-metallic enclosure, with thermal overload relay, with START and STOP/RESET buttons

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Electromechanical starters - LOVATO ELECTRIC

## Additional Product Information

M0P00912460605

Direct-on-line-starter, 3...5A (1.5...2.2kW at 400V), IP65, contactor coil voltage 460VAC 60Hz, non-metallic enclosure, with thermal overload relay, with START and STOP/RESET buttons

Technical specifications

Type of product:Direct-on-line-startersIEC operating current and power Ie (AC3) 400V [A/Kw]:5A / 2.2kWUL/CSA

horsepower ratings 480V [HP]:3Type:Enclosed with thermal overload relayType of coil:AC coilType of pushbutton:With

Start-Stop/Reset buttonsContactor coil voltage:460VAC 60HZOrder code M0P00912460605

Weight [g] 760

Qty. per package 1  
Multiple qty. of packs per order 1  
Package dimensions [mm] 187X092X160  
Volume [cm<sup>3</sup>] 2752.64  
Bar code [EAN13] 8013975179949  
HS Code 85371098  
203.77 £  
ETIM for M0P00912460605 Low-voltage industrial controls and switchgear (EC001037)  
Feature Name  
Feature Value  
Degree of protection (NEMA) (EF011959)  
4X  
Type of motor starter (EF009598)  
Direct starter  
Voltage type for actuating (EF008242)  
AC  
Type of electrical connection for auxiliary- and control current circuit (EF006979)  
Screw connection  
Type of electrical connection of main circuit (EF006819)  
Screw connection  
Release class (EF006668)  
CLASS 10 A  
Degree of protection (IP) (EF005474)  
IP65  
Rated control supply voltage AC 60 Hz (EF003979)  
460 V  
Overload release current setting (EF002336)  
3 A  
Temperature compensated overload protection (EF009604)  
Yes  
Supporting protocol for SafetyBUS p (EF007527)  
No  
Supporting protocol for PROFI-safe (EF007526)  
No  
Supporting protocol for PROFINET...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / M0P00912460605 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.