

INDUSTRIAL COMPONENT DATA

M1P0091246060A6 LOVATO DOL STARTER M1P 460/60 1.6-2.5A

Brand: LOVATO ELECTRIC | Manufacturer Part Number: M1P0091246060A6



Manufacturer	LOVATO ELECTRIC
MPN / Reference	M1P0091246060A6
Catalog number	M1P0091246060A6
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-EF932361B3
Generated	2026-08-04

Product Overview

DOL STARTER M1P 460/60 1.6-2.5A

Direct-on-line-starter, 1.6...2.5A (0.75kW at 400V), IP65, contactor coil voltage 460VAC 60Hz, non-metallic enclosure, with thermal overload relay, with START and STOP/RESET buttons

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Electromechanical starters - LOVATO ELECTRIC

Additional Product Information

M1P0091246060A6

Direct-on-line-starter, 1.6...2.5A (0.75kW at 400V), IP65, contactor coil voltage 460VAC 60Hz, non-metallic enclosure, with thermal overload relay, with START and STOP/RESET buttons

Technical specifications

Type of product:Direct-on-line-startersIEC operating current and power Ie (AC3) 400V [A/Kw]:2.5A / 0.75kWUL/CSA horsepower ratings 480V [HP]:1Type:Enclosed with thermal overload relayType of coil:AC coilOrder code

M1P0091246060A6

Weight [g] 1032

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 206X092X170

Volume [cm³] 3221.84

Bar code [EAN13] 8013975220177

HS Code 85371098

210.33 £

ETIM for M1P0091246060A6 Low-voltage industrial controls and switchgear (EC001037)

Feature Name

Feature Value

Degree of protection (NEMA) (EF011959)

4X

Type of motor starter (EF009598)

Direct starter

Voltage type for actuating (EF008242)

AC

Type of electrical connection for auxiliary- and control current circuit (EF006979)

Screw connection

Type of electrical connection of main circuit (EF006819)

Screw connection

Release class (EF006668)

CLASS 10 A

Degree of protection (IP) (EF005474)

IP65

Rated control supply voltage AC 60 Hz (EF003979)

460 V

Overload release current setting (EF002336)

1.6 A

Temperature compensated overload protection (EF009604)

Yes

Supporting protocol for SafetyBUS p (EF007527)

No

Supporting protocol for PROFIsafe (EF007526)

No

Supporting protocol for PROFINET IO (EF007525)

No

Supporting protocol for PROFINET CBA (EF007524)

No

Support...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / M1P0091246060A6 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.