

INDUSTRIAL COMPONENT DATA

M25P03812230B5 LOVATO Starter direct in box with push-up and shutdown/reset, with relay thermal 38A 230V AC

Brand: LOVATO ELECTRIC | Manufacturer Part Number: M25P03812230B5



Manufacturer	LOVATO ELECTRIC
MPN / Reference	M25P03812230B5
Catalog number	03812230
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-637AECE764
Generated	2026-08-06

Product Overview

Starter direct in box with push-up and shutdown/reset, with relay thermal 38A 230V AC

DOL STARTER M25P 230/50-60 38A

Direct-on-line-starter, 32...38A (18,5kW at 400V), IP65, contactor coil voltage 230VAC 50/60Hz, non-metallic enclosure, with thermal overload relay, with START and STOP/RESET buttons

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LOVATO ELECTRIC > Electromechanical starters - LOVATO ELECTRIC
--------------	--

Additional Product Information

M25P03812230B5

Direct-on-line-starter, 32...38A (18,5kW at 400V), IP65, contactor coil voltage 230VAC 50/60Hz, non-metallic enclosure, with thermal overload relay, with START and STOP/RESET buttons

Technical specifications

Type of product:Direct-on-line-startersIEC operating current and power Ie (AC3) 400V [A/Kw]:38A / 18.5kWUL/CSA

horsepower ratings 480V [HP]:30Type:Enclosed with thermal overload relayType of coil:AC coilOrder code

M25P03812230B5

Weight [g] 1911.9

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 222X175X195

Volume [cm³] 7575.75

Bar code [EAN13] 8013975213353
HS Code 85371098
426.6 £
ETIM for M25P03812230B5 Low-voltage industrial controls and switchgear (EC001037)
Feature Name
Feature Value
Degree of protection (NEMA) (EF011959)
4X
Type of motor starter (EF009598)
Direct starter
Voltage type for actuating (EF008242)
AC
Type of electrical connection for auxiliary- and control current circuit (EF006979)
Screw connection
Type of electrical connection of main circuit (EF006819)
Screw connection
Release class (EF006668)
CLASS 10 A
Degree of protection (IP) (EF005474)
IP65
Rated control supply voltage AC 60 Hz (EF003979)
230 V
Rated control supply voltage AC 50 Hz (EF003978)
230 V
Overload release current setting (EF002336)
32 A
Temperature compensated overload protection (EF009604)
Yes
Supporting protocol for SafetyBUS p (EF007527)
No
Supporting protocol for PROFIsafe (EF007526)
No
Supporting protocol for PROFINET IO (EF007525)
No
Suppo...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / M25P03812230B5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.