

INDUSTRIAL COMPONENT DATA

M25P03812400B5 LOVATO Starter direct in box with push-up and shutdown/reset, with relay thermal 38A 400V AC

Brand: LOVATO ELECTRIC | Manufacturer Part Number: M25P03812400B5



Manufacturer	LOVATO ELECTRIC
MPN / Reference	M25P03812400B5
Catalog number	03812400
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-C59F0DE3D6
Generated	2026-08-04

Product Overview

Starter direct in box with push-up and shutdown/reset, with relay thermal 38A 400V AC

DOL STARTER M25P 400/50-60 38A

Direct-on-line-starter, 32...38A (18,5kW at 400V), IP65, contactor coil voltage 400VAC 50/60Hz, non-metallic enclosure, with thermal overload relay, with START and STOP/RESET buttons

DIRECT STARTER, 32...38A (18.5KW AT 400V), CONTACTOR COIL VOLTAGE 400VAC 50/60HZ, WITH THERMAL RELAY IN IP65 INSULATED ENCLOSURE, WITH START AND STOP/RESET BUTTONS,

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LOVATO ELECTRIC > Electromechanical starters - LOVATO ELECTRIC
--------------	--

Additional Product Information

M25P03812400B5

Direct-on-line-starter, 32...38A (18,5kW at 400V), IP65, contactor coil voltage 400VAC 50/60Hz, non-metallic enclosure, with thermal overload relay, with START and STOP/RESET buttons

Technical specifications

Type of product:Direct-on-line-startersIEC operating current and power Ie (AC3) 400V [A/Kw]:38A / 18.5kWUL/CSA horsepower ratings 480V [HP]:30Type:Enclosed with thermal overload relayType of coil:AC coilOrder code

M25P03812400B5

Weight [g] 2880

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 295X240X225
Volume [cm³] 15930
Bar code [EAN13] 8013975216675
HS Code 85371098
ETIM for M25P03812400B5 Low-voltage industrial controls and switchgear (EC001037)
Feature Name
Feature Value
Degree of protection (NEMA) (EF011959)
4X
Type of motor starter (EF009598)
Direct starter
Voltage type for actuating (EF008242)
AC
Type of electrical connection for auxiliary- and control current circuit (EF006979)
Screw connection
Type of electrical connection of main circuit (EF006819)
Screw connection
Release class (EF006668)
CLASS 10 A
Degree of protection (IP) (EF005474)
IP65
Rated control supply voltage AC 60 Hz (EF003979)
240 V
Rated control supply voltage AC 50 Hz (EF003978)
240 V
Overload release current setting (EF002336)
32 A
Temperature compensated overload protection (EF009604)
Yes
Supporting protocol for SafetyBUS p (EF007527)
No
Supporting protocol for PROFIsafe (EF007526)
No
Supporting protocol for PROFINET IO (EF007525)
No
Supporting protoc...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / M25P03812400B5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.