

INDUSTRIAL COMPONENT DATA

M2P0091102460A6 LOVATO DOL STARTER M2P 24V 60HZ WITH SMR 1,6-2,

Brand: LOVATO ELECTRIC | Manufacturer Part Number: M2P0091102460A6



Manufacturer	LOVATO ELECTRIC
MPN / Reference	M2P0091102460A6
Catalog number	0091102460
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-82D9062F41
Generated	2026-08-03

Product Overview

DOL STARTER M2P 24V 60HZ WITH SMR 1,6-2,

Direct-on-line-starter, enclosed with motor protection circuit breaker, 2.5A ($\leq 440V$), IP65. Contactor coil voltage 24VAC 60Hz

DIRECT STARTER, WITH MOTOR PROTECTION SWITCH IN INSULATED CASE, 2.5A ($\leq 440V$), IP65. CONTACTOR COIL VOLTAGE 24VAC 60HZ

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Electromechanical starters - LOVATO ELECTRIC

Additional Product Information

M2P0091102460A6

Direct-on-line-starter, enclosed with motor protection circuit breaker, 2.5A ($\leq 440V$), IP65. Contactor coil voltage 24VAC 60Hz

Technical specifications

Type of product:Direct-on-line-startersIEC operating current and power I_e (AC3) 400V [A/Kw]:2.5A / 0.75kWUL/CSA horsepower ratings 480V [HP]:1Type:Enclosed with motor protection circuit breakerType of coil:AC coilContactor coil voltage:24VAC 60HZOrder code M2P0091102460A6

Weight [g] 1300

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 238X114X188

Volume [cm³] 5100.816
Bar code [EAN13] 8013975266977
HS Code 85371098
424.04 £
ETIM for M2P0091102460A6 Low-voltage industrial controls and switchgear (EC001037)
Feature Name
Feature Value
Degree of protection (NEMA) (EF011959)
4X
Type of motor starter (EF009598)
Direct starter
Voltage type for actuating (EF008242)
AC
Type of electrical connection for auxiliary- and control current circuit (EF006979)
Screw connection
Type of electrical connection of main circuit (EF006819)
Screw connection
Release class (EF006668)
CLASS 10 A
Degree of protection (IP) (EF005474)
IP65
Rated control supply voltage AC 60 Hz (EF003979)
24 V
Overload release current setting (EF002336)
1.6 A
Temperature compensated overload protection (EF009604)
Yes
Supporting protocol for SafetyBUS p (EF007527)
No
Supporting protocol for PROFIsafe (EF007526)
No
Supporting protocol for PROFINET IO (EF007525)
No
Supporting protocol for PROFINET CBA (EF007524)
No
Supporting protoco...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / M2P0091102460A6 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.