

INDUSTRIAL COMPONENT DATA

M2P00911400A5 LOVATO DIRECT-ON-LINE STARTER, ENCLOSED WITH MOTOR PROTECTION CIRCUIT BREAKERS, 1.6A (<=440V), ..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: M2P00911400A5



Manufacturer	LOVATO ELECTRIC
MPN / Reference	M2P00911400A5
Catalog number	00911400
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-300143023B
Generated	2026-08-02

Product Overview

DIRECT-ON-LINE STARTER, ENCLOSED WITH MOTOR PROTECTION CIRCUIT BREAKERS, 1.6A (<=440V), IP65.

CONTACTOR COIL VOLTAGE 400VAC 50/60HZ

DOL STARTER M2P 400V WITH SMR 1-1,6A

Direct-on-line-starter, enclosed with motor protection circuit breaker, 1.6A (<=440V), IP65. Contactor coil voltage 400VAC 50/60Hz

DIRECT STARTER, WITH MOTOR PROTECTION SWITCH IN INSULATED HOUSING, 1.6A (?440V), IP65.

CONTACTOR COIL VOLTAGE 400VAC 50/60HZ

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LOVATO ELECTRIC > Electromechanical starters - LOVATO ELECTRIC
--------------	--

Additional Product Information

M2P00911400A5

Direct-on-line-starter, enclosed with motor protection circuit breaker, 1.6A (<=440V), IP65. Contactor coil voltage 400VAC 50/60Hz

Technical specifications

Type of product:Direct-on-line-startersIEC operating current and power Ie (AC3) 400V [A/Kw]:1.6A / 0.55kWUL/CSA

horsepower ratings 480V [HP]:0.75Type:Enclosed with motor protection circuit breakerType of coil:AC coilContactor coil voltage:400VAC 50/60HZOrder code M2P00911400A5

Weight [g] 1300.7
Qty. per package 1
Multiple qty. of packs per order 1
Package dimensions [mm] 238X114X188
Volume [cm³] 5100.816
Bar code [EAN13] 8013975226926
HS Code 85371098
249.12 £
ETIM for M2P00911400A5 Low-voltage industrial controls and switchgear (EC001037)
Feature Name
Feature Value
Degree of protection (NEMA) (EF011959)
4X
Type of motor starter (EF009598)
Direct starter
Voltage type for actuating (EF008242)
AC
Type of electrical connection for auxiliary- and control current circuit (EF006979)
Screw connection
Type of electrical connection of main circuit (EF006819)
Screw connection
Release class (EF006668)
CLASS 10 A
Degree of protection (IP) (EF005474)
IP65
Rated control supply voltage AC 60 Hz (EF003979)
400 V
Rated control supply voltage AC 50 Hz (EF003978)
400 V
Overload release current setting (EF002336)
1 A
Temperature compensated overload protection (EF009604)
Yes
Supporting protocol for SafetyBUS p (EF007527)
No
Supporting protocol for PROFIsafe (EF007526)
No
Supporting protocol for PROFINET IO (EF007525)
No
Supporti...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / M2P00911400A5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.