

INDUSTRIAL COMPONENT DATA

M2P00911400A8 LOVATO DIRECT-ON-LINE STARTER, ENCLOSED WITH MOTOR PROTECTION CIRCUIT BREAKERS, 6.5A ($\leq 440V$), ..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: M2P00911400A8



Manufacturer	LOVATO ELECTRIC
MPN / Reference	M2P00911400A8
Catalog number	00911400
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-0898530B15
Generated	2026-08-04

Product Overview

DIRECT-ON-LINE STARTER, ENCLOSED WITH MOTOR PROTECTION CIRCUIT BREAKERS, 6.5A ($\leq 440V$), IP65.

CONTACTOR COIL VOLTAGE 400VAC 50/60HZ

DOL STARTER M2P 400V WITH SMR 4-6,5A

Direct-on-line-starter, enclosed with motor protection circuit breaker, 6.5A ($\leq 440V$), IP65. Contactor coil voltage 400VAC 50/60Hz

DIRECT STARTER, WITH MOTOR PROTECTION SWITCH IN INSULATED CASE, 6.5A ($\leq 440V$), IP65. CONTACTOR COIL VOLTAGE 400VAC 50/60HZ

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LOVATO ELECTRIC > Electromechanical starters - LOVATO ELECTRIC
--------------	--

Additional Product Information

M2P00911400A8

Direct-on-line-starter, enclosed with motor protection circuit breaker, 6.5A ($\leq 440V$), IP65. Contactor coil voltage 400VAC 50/60Hz

Technical specifications

Type of product:Direct-on-line-startersIEC operating current and power I_e (AC3) 400V [A/Kw]:6.5A / 3kWUL/CSA

horsepower ratings 480V [HP]:3Type:Enclosed with motor protection circuit breakerType of coil:AC coilContactor coil voltage:400VAC 50/60HZOrder code M2P00911400A8

Weight [g] 1297

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 238X114X188

Volume [cm³] 5100.816

Bar code [EAN13] 8013975226957

HS Code 85371098

249.12 £

ETIM for M2P00911400A8 Low-voltage industrial controls and switchgear (EC001037)

Feature Name

Feature Value

Degree of protection (NEMA) (EF011959)

4X

Type of motor starter (EF009598)

Direct starter

Voltage type for actuating (EF008242)

AC

Type of electrical connection for auxiliary- and control current circuit (EF006979)

Screw connection

Type of electrical connection of main circuit (EF006819)

Screw connection

Release class (EF006668)

CLASS 10 A

Degree of protection (IP) (EF005474)

IP65

Rated control supply voltage AC 60 Hz (EF003979)

400 V

Rated control supply voltage AC 50 Hz (EF003978)

400 V

Overload release current setting (EF002336)

4 A

Temperature compensated overload protection (EF009604)

Yes

Supporting protocol for SafetyBUS p (EF007527)

No

Supporting protocol for PROFIsafe (EF007526)

No

Supporting protocol for PROFINET IO (EF007525)

No

Supporting proto...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / M2P00911400A8 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.