

INDUSTRIAL COMPONENT DATA

M2P0251223060B2 LOVATO DOL STARTER M2P 230/60 17-23A

Brand: LOVATO ELECTRIC | Manufacturer Part Number: M2P0251223060B2



Manufacturer	LOVATO ELECTRIC
MPN / Reference	M2P0251223060B2
Catalog number	0251223060
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-C7921A6DD6
Generated	2026-08-01

Product Overview

DOL STARTER M2P 230/60 17-23A

Direct-on-line-starter, 17...23A (11kW at 400V), IP65, contactor coil voltage 230VAC 60Hz, non-metallic enclosure, with thermal overload relay, with START and STOP/RESET buttons

DIRECT STARTER, 17 23A (11KW AT 400V), CONTACTOR COIL VOLTAGE 230VAC 60HZ, WITH THERMAL RELAY IN IP65 INSULATED CASE, WITH START AND STOP/RESET BUTTONS,

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

LOVATO ELECTRIC > Electromechanical starters - LOVATO ELECTRIC

Additional Product Information

M2P0251223060B2

Direct-on-line-starter, 17...23A (11kW at 400V), IP65, contactor coil voltage 230VAC 60Hz, non-metallic enclosure, with thermal overload relay, with START and STOP/RESET buttons

Technical specifications

Type of product:Direct-on-line-startersIEC operating current and power Ie (AC3) 400V [A/Kw]:23A / 11kWUL/CSA

horsepower ratings 480V [HP]:15Type:Enclosed without thermal overload relayType of coil:AC coilOrder code

M2P0251223060B2

Weight [g] 1220

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 238X114X188

Volume [cm³] 5100.816
Bar code [EAN13] 8013975246092
HS Code 85371098
ETIM for M2P0251223060B2 Low-voltage industrial controls and switchgear (EC001037)
Feature Name
Feature Value
Degree of protection (NEMA) (EF011959)
4X
Type of motor starter (EF009598)
Direct starter
Voltage type for actuating (EF008242)
AC
Type of electrical connection for auxiliary- and control current circuit (EF006979)
Screw connection
Type of electrical connection of main circuit (EF006819)
Screw connection
Release class (EF006668)
CLASS 10 A
Degree of protection (IP) (EF005474)
IP65
Rated control supply voltage AC 60 Hz (EF003979)
230 V
Overload release current setting (EF002336)
17 A
Temperature compensated overload protection (EF009604)
Yes
Supporting protocol for SafetyBUS p (EF007527)
No
Supporting protocol for PROFIsafe (EF007526)
No
Supporting protocol for PROFINET IO (EF007525)
No
Supporting protocol for PROFINET CBA (EF007524)
No
Supporting protoc...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / M2P0251223060B2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.