

INDUSTRIAL COMPONENT DATA

M3P00973230 LOVATO Starter star-delta, in box with disconnecter, without thermal relay 16A-coil 230 v AC

Brand: LOVATO ELECTRIC | Manufacturer Part Number: M3P00973230



Manufacturer	LOVATO ELECTRIC
MPN / Reference	M3P00973230
Catalog number	00973230
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-D029C4A584
Generated	2026-08-04

Product Overview

Starter star-delta, in box with disconnecter, without thermal relay 16A-coil 230 v AC

S-D STARTER22A 230/50-60 C/W CASE+SWITCH

Star-delta starter, enclosed starter, with switch disconnecter, rotary door coupling handle GAX61 and START and STOP/RESET buttons. Starting time up to 12 seconds and a maximum of 30 operations/hour, max IEC operating current 16A. Coil voltage 230VAC 50/60Hz

STAR-DELTA STARTER, IN INSULATED CASE, WITH START AND STOP/RESET BUTTONS. START-UP TIMES UP TO 12 SEC. AND A MAXIMUM OF 30 MANOEUVRES/HOUR, MAX OPERATING CURRENT 16A. COIL VOLTAGE 230VAC 50/60HZ

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

LOVATO ELECTRIC > Electromechanical starters - LOVATO ELECTRIC

Additional Product Information

M3P00973230

Star-delta starter, enclosed starter, with switch disconnecter, rotary door coupling handle GAX61 and START and STOP/RESET buttons. Starting time up to 12 seconds and a maximum of 30 operations/hour, max IEC operating current 16A. Coil voltage 230VAC 50/60Hz

Technical specifications

Type of product: Empty non-metallic enclosuresUL/CSA horsepower ratings 480V [HP]: 7.5Order code M3P00973230

Weight [g] 3.7

Qty. per package 1

Multiple qty. of packs per order 1
Package dimensions [mm] 295X240X225
Volume [cm³] 15930
Bar code [EAN13] 8013975227138
HS Code 85371098
ETIM for M3P00973230 Low-voltage industrial controls and switchgear (EC001037)
Feature Name
Feature Value
Degree of protection (NEMA) (EF011959)
4X
Type of motor starter (EF009598)
Star-delta starter
Voltage type for actuating (EF008242)
AC
Type of electrical connection for auxiliary- and control current circuit (EF006979)
Screw connection
Type of electrical connection of main circuit (EF006819)
Screw connection
Release class (EF006668)
CLASS 10 A
Degree of protection (IP) (EF005474)
IP65
Rated control supply voltage AC 60 Hz (EF003979)
230 V
Rated control supply voltage AC 50 Hz (EF003978)
230 V
Temperature compensated overload protection (EF009604)
Yes
Supporting protocol for SafetyBUS p (EF007527)
No
Supporting protocol for PROFIsafe (EF007526)
No
Supporting protocol for PROFINET IO (EF007525)
No
Supporting protocol for PROFINET CBA (EF007524)
No
Supporting protocol for Foundation Fieldbus (EF007522)
No
Supp...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / M3P00973230 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.