

## INDUSTRIAL COMPONENT DATA

# M3P03273230 LOVATO Starter star-delta, in box with disconnecter, without thermal relay 50A coil 230V AC

Brand: LOVATO ELECTRIC | Manufacturer Part Number: M3P03273230



|                 |                                         |
|-----------------|-----------------------------------------|
| Manufacturer    | LOVATO ELECTRIC                         |
| MPN / Reference | M3P03273230                             |
| Catalog number  | 03273230                                |
| Category        | Motor starter/Motor starter combination |
| Minimum order   | 1 Pcs                                   |
| Document ID     | EO-25EA23598E                           |
| Generated       | 2026-08-04                              |

## Product Overview

Starter star-delta, in box with disconnecter, without thermal relay 50A coil 230V AC

SDS 50A 230V 50/60HZ W/CASE+SWITCH

Star-delta starter, enclosed starter, with switch disconnecter, rotary door coupling handle GAX61 and START and STOP/RESET buttons. Starting time up to 12 seconds and a maximum of 30 operations/hour, max IEC operating current 50A. Coil voltage 230VAC 50/60Hz

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Electromechanical starters - LOVATO ELECTRIC

## Additional Product Information

M3P03273230

Star-delta starter, enclosed starter, with switch disconnecter, rotary door coupling handle GAX61 and START and STOP/RESET buttons. Starting time up to 12 seconds and a maximum of 30 operations/hour, max IEC operating current 50A. Coil voltage 230VAC 50/60Hz

Technical specifications

Type of product:Empty non-metallic enclosuresUL/CSA horsepower ratings 480V [HP]:30Order code M3P03273230

Weight [g] 3820

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 295X240X225

Volume [cm³] 15930

Bar code [EAN13] 8013975218358  
HS Code 85371098  
ETIM for M3P03273230 Low-voltage industrial controls and switchgear (EC001037)  
Feature Name  
Feature Value  
Degree of protection (NEMA) (EF011959)  
4X  
Type of motor starter (EF009598)  
Star-delta starter  
Voltage type for actuating (EF008242)  
AC  
Type of electrical connection for auxiliary- and control current circuit (EF006979)  
Screw connection  
Type of electrical connection of main circuit (EF006819)  
Screw connection  
Release class (EF006668)  
CLASS 10 A  
Degree of protection (IP) (EF005474)  
IP65  
Rated control supply voltage AC 60 Hz (EF003979)  
230 V  
Rated control supply voltage AC 50 Hz (EF003978)  
230 V  
Temperature compensated overload protection (EF009604)  
Yes  
Supporting protocol for SafetyBUS p (EF007527)  
No  
Supporting protocol for PROFI-safe (EF007526)  
No  
Supporting protocol for PROFINET IO (EF007525)  
No  
Supporting protocol for PROFINET CBA (EF007524)  
No  
Supporting protocol for Foundation Fieldbus (EF007522)  
No  
Supp...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / M3P03273230 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.