

INDUSTRIAL COMPONENT DATA

M3P03273230 LOVATO Starter star-delta, in box with disconnecter, without thermal relay 50A coil 230V AC

Brand: LOVATO ELECTRIC | Manufacturer Part Number: M3P03273230



Manufacturer	LOVATO ELECTRIC
MPN / Reference	M3P03273230
Catalog number	03273230
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-25EA23598E
Generated	2026-08-06

Product Overview

Starter star-delta, in box with disconnecter, without thermal relay 50A coil 230V AC

SDS 50A 230V 50/60HZ W/CASE+SWITCH

Star-delta starter, enclosed starter, with switch disconnecter, rotary door coupling handle GAX61 and START and STOP/RESET buttons. Starting time up to 12 seconds and a maximum of 30 operations/hour, max IEC operating current 50A. Coil voltage 230VAC 50/60Hz

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Electromechanical starters - LOVATO ELECTRIC

Additional Product Information

M3P03273230

Star-delta starter, enclosed starter, with switch disconnecter, rotary door coupling handle GAX61 and START and STOP/RESET buttons. Starting time up to 12 seconds and a maximum of 30 operations/hour, max IEC operating current 50A. Coil voltage 230VAC 50/60Hz

Technical specifications

Type of product: Empty non-metallic enclosures UL/CSA horsepower ratings 480V [HP]: 30 Order code M3P03273230

Weight [g] 3820

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 295X240X225

Volume [cm³] 15930

Bar code [EAN13] 8013975218358
HS Code 85371098
ETIM for M3P03273230 Low-voltage industrial controls and switchgear (EC001037)
Feature Name
Feature Value
Degree of protection (NEMA) (EF011959)
4X
Type of motor starter (EF009598)
Star-delta starter
Voltage type for actuating (EF008242)
AC
Type of electrical connection for auxiliary- and control current circuit (EF006979)
Screw connection
Type of electrical connection of main circuit (EF006819)
Screw connection
Release class (EF006668)
CLASS 10 A
Degree of protection (IP) (EF005474)
IP65
Rated control supply voltage AC 60 Hz (EF003979)
230 V
Rated control supply voltage AC 50 Hz (EF003978)
230 V
Temperature compensated overload protection (EF009604)
Yes
Supporting protocol for SafetyBUS p (EF007527)
No
Supporting protocol for PROFI-safe (EF007526)
No
Supporting protocol for PROFINET IO (EF007525)
No
Supporting protocol for PROFINET CBA (EF007524)
No
Supporting protocol for Foundation Fieldbus (EF007522)
No
Supp...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / M3P03273230 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.