

INDUSTRIAL COMPONENT DATA

M3P0387022060 LOVATO SDS 60A 220V 60HZ W/CASE

Brand: LOVATO ELECTRIC | Manufacturer Part Number: M3P0387022060



Manufacturer	LOVATO ELECTRIC
MPN / Reference	M3P0387022060
Catalog number	0387022060
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-B9FDA399EC
Generated	2026-08-04

Product Overview

SDS 60A 220V 60HZ W/CASE

Star-delta starter, enclosed starter, with START and STOP/RESET buttons. Starting time up to 12 seconds and a maximum of 30 operations/hour, max IEC operating current 60A. Coil voltage 220VAC 60Hz

STAR-DELTA STARTER, IN INSULATED CASE, WITH START AND STOP/RESET BUTTONS. START-UP TIMES UP TO 12 SEC. AND A MAXIMUM OF 30 MANOEUVRES/HOUR, MAXIMUM OPERATING CURRENT 60A. COIL VOLTAGE 220VAC 60HZ

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **LOVATO ELECTRIC > Electromechanical starters - LOVATO ELECTRIC**

Additional Product Information

M3P0387022060

Star-delta starter, enclosed starter, with START and STOP/RESET buttons. Starting time up to 12 seconds and a maximum of 30 operations/hour, max IEC operating current 60A. Coil voltage 220VAC 60Hz

Technical specifications

Type of product:Empty non-metallic enclosuresUL/CSA horsepower ratings 480V [HP]:50Order code M3P0387022060

Weight [g] 3700

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 295X240X225

Volume [cm³] 15930

Bar code [EAN13] 8013975231654

HS Code 85371098

ETIM for M3P0387022060 Low-voltage industrial controls and switchgear (EC001037)

Feature Name

Feature Value

Degree of protection (NEMA) (EF011959)

4X

Type of motor starter (EF009598)

Star-delta starter

Voltage type for actuating (EF008242)

AC

Type of electrical connection for auxiliary- and control current circuit (EF006979)

Screw connection

Type of electrical connection of main circuit (EF006819)

Screw connection

Release class (EF006668)

CLASS 10 A

Degree of protection (IP) (EF005474)

IP65

Rated control supply voltage AC 60 Hz (EF003979)

220 V

Temperature compensated overload protection (EF009604)

Yes

Supporting protocol for SafetyBUS p (EF007527)

No

Supporting protocol for PROFIsafe (EF007526)

No

Supporting protocol for PROFINET IO (EF007525)

No

Supporting protocol for PROFINET CBA (EF007524)

No

Supporting protocol for Foundation Fieldbus (EF007522)

No

Supporting protocol for EtherNet/IP (EF007521)

No

Supporting protocol for DeviceNet Safety (EF007520)

No

Supporting...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / M3P0387022060 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.