

INDUSTRIAL COMPONENT DATA

M3P06512024B7 LOVATO Starter direct in box with push-up and shutdown/reset, with thermal relay 65A 24V AC

Brand: LOVATO ELECTRIC | Manufacturer Part Number: M3P06512024B7



Manufacturer	LOVATO ELECTRIC
MPN / Reference	M3P06512024B7
Catalog number	06512024
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-EA02D8CE34
Generated	2026-08-05

Product Overview

Starter direct in box with push-up and shutdown/reset, with thermal relay 65A 24V AC

DOL STARTER M3P 24/50-60 65A

Direct-on-line-starter, 45...65A (30kW at 400VAC), IP65, contactor coil voltage 120VAC 50/60Hz, non-metallic enclosure, with thermal overload relay, with START and STOP/RESET buttons

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Electromechanical starters - LOVATO ELECTRIC

Additional Product Information

M3P06512024B7

Direct-on-line-starter, 45...65A (30kW at 400VAC), IP65, contactor coil voltage 120VAC 50/60Hz, non-metallic enclosure, with thermal overload relay, with START and STOP/RESET buttons

Technical specifications

Type of product:Direct-on-line-startersIEC operating current and power Ie (AC3) 400V [A/Kw]:65A / 30kWUL/CSA

horsepower ratings 480V [HP]:50Type:Enclosed with thermal overload relayType of coil:AC coilOrder code

M3P06512024B7

Weight [g] 3820

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 295X240X225

Volume [cm³] 15930

Bar code [EAN13] 8013975214107
HS Code 85371098
ETIM for M3P06512024B7 Low-voltage industrial controls and switchgear (EC001037)
Feature Name
Feature Value
Degree of protection (NEMA) (EF011959)
4X
Type of motor starter (EF009598)
Direct starter
Voltage type for actuating (EF008242)
AC
Type of electrical connection for auxiliary- and control current circuit (EF006979)
Screw connection
Type of electrical connection of main circuit (EF006819)
Screw connection
Release class (EF006668)
CLASS 10 A
Degree of protection (IP) (EF005474)
IP65
Rated control supply voltage AC 60 Hz (EF003979)
24 V
Rated control supply voltage AC 50 Hz (EF003978)
24 V
Overload release current setting (EF002336)
46 A
Temperature compensated overload protection (EF009604)
Yes
Supporting protocol for SafetyBUS p (EF007527)
No
Supporting protocol for PROFI-safe (EF007526)
No
Supporting protocol for PROFINET IO (EF007525)
No
Supporting protocol fo...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / M3P06512024B7 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.