

INDUSTRIAL COMPONENT DATA

M3P0651222060B7 LOVATO DOL STARTER M3P 220/60 65A

Brand: LOVATO ELECTRIC | Manufacturer Part Number: M3P0651222060B7



Manufacturer	LOVATO ELECTRIC
MPN / Reference	M3P0651222060B7
Catalog number	M3P0651222060B7
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-2EAC69BD3E
Generated	2026-08-04

Product Overview

DOL STARTER M3P 220/60 65A

Direct-on-line-starter, 45...65A (30kW at 400VAC), IP65, contactor coil voltage 220VAC 60Hz, non-metallic enclosure, with thermal overload relay, with START and STOP/RESET button

DIRECT STARTER, 45...65A (30KW AT 400V), CONTACTOR COIL VOLTAGE 220VAC 60HZ, WITH THERMAL RELAY IN IP65 INSULATED ENCLOSURE, WITH START AND STOP/RESET BUTTONS,

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **LOVATO ELECTRIC > Electromechanical starters - LOVATO ELECTRIC**

Additional Product Information

M3P0651222060B7

Direct-on-line-starter, 45...65A (30kW at 400VAC), IP65, contactor coil voltage 220VAC 60Hz, non-metallic enclosure, with thermal overload relay, with START and STOP/RESET button

Technical specifications

Type of product:Direct-on-line-startersIEC operating current and power Ie (AC3) 400V [A/Kw]:65A / 30kWUL/CSA horsepower ratings 480V [HP]:50Type:Enclosed with thermal overload relayType of coil:AC coilOrder code

M3P0651222060B7

Weight [g] 3820

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 295X240X225

Volume [cm³] 15930

Bar code [EAN13] 8013975218549

HS Code 85371098

ETIM for M3P0651222060B7 Low-voltage industrial controls and switchgear (EC001037)

Feature Name

Feature Value

Degree of protection (NEMA) (EF011959)

4X

Type of motor starter (EF009598)

Direct starter

Voltage type for actuating (EF008242)

AC

Type of electrical connection for auxiliary- and control current circuit (EF006979)

Screw connection

Type of electrical connection of main circuit (EF006819)

Screw connection

Release class (EF006668)

CLASS 10 A

Degree of protection (IP) (EF005474)

IP65

Rated control supply voltage AC 60 Hz (EF003979)

220 V

Rated control supply voltage AC 50 Hz (EF003978)

220 V

Overload release current setting (EF002336)

46 A

Temperature compensated overload protection (EF009604)

Yes

Supporting protocol for SafetyBUS p (EF007527)

No

Supporting protocol for PROFI-safe (EF007526)

No

Supporting protocol for PROFINET IO (EF007525)

No

Supporting protoco...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / M3P0651222060B7 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.