

INDUSTRIAL COMPONENT DATA

ME024FSD024 LOVATO ELECTRONIC. DOL STARTER WITH STO 24VDC 2.4A

Brand: LOVATO ELECTRIC | Manufacturer Part Number: ME024FSD024



Manufacturer	LOVATO ELECTRIC
MPN / Reference	ME024FSD024
Catalog number	ME024FSD024
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-9461F11E15
Generated	2026-08-03

Product Overview

ELECTRONIC. DOL STARTER WITH STO 24VDC 2.4A

Electronic direct-on-line starter, 2.4A, integrated motor thermal protection and STO (Safe Torque Off) emergency stop, operational voltage $U_e \leq 500VAC$, auxiliary and control supply voltage 24VDC

AVVIAT. DIR. ELETTR. CON STO 24VDC 2.4A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Electromechanical starters - LOVATO ELECTRIC

Additional Product Information

ME024FSD024

Electronic direct-on-line starter, 2.4A, integrated motor thermal protection and STO (Safe Torque Off) emergency stop, operational voltage $U_e \leq 500VAC$, auxiliary and control supply voltage 24VDC

Technical specifications

Type of product:Electronic motor starterFunctions:Direct-On-Line starterSafe torque Off (STO) safety

function:Built-inThermal protection:Integrated, class 10AIEC operating current and power I_e (AC3) 400V

[A/Kw]:2.4Type:Electronic direct-on-line starter, 2.4A, integrated motor thermal protection and STO (Safe Torque Off) emergency stopOrder code ME024FSD024

Weight [g] 300

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 150X120X30

Volume [cm³] 540
Bar code [EAN13] 8013975320983
HS Code 85365003
204.36 £
ETIM for ME024FSD024 Low-voltage industrial controls and switchgear (EC001037)
Feature Name
Feature Value
Rated control supply voltage DC (EF003980)
24 V
Overload release current setting (EF002336)
0.18 A
Ambient temperature, upper operating limit (EF009603)
50 °C
Rated operation current at AC-3, 400 V (EF009602)
2.4 A
Rated power, 460 V, 60 Hz, 3-phase (EF009600)
0.75 kW
Number of indicator lights (EF001965)
3
Rated operation current I_e (EF001443)
2.4 A
Number of auxiliary contacts as normally closed contact (EF001377)
2
Rated operation power at AC-3, 400 V (EF001364)
0.75 kW
Depth (EF000049)
140 mm
Height (EF000040)
100 mm
Width (EF000008)
22.5 mm
Temperature compensated overload protection (EF009604)
Yes
Supporting pro...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / ME024FSD024 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.