

INDUSTRIAL COMPONENT DATA

ME070FD024 LOVATO ELECTRONIC DOL STARTER 24VDC 7A

Brand: LOVATO ELECTRIC | Manufacturer Part Number: ME070FD024



Manufacturer	LOVATO ELECTRIC
MPN / Reference	ME070FD024
Catalog number	ME070FD024
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-C0E9F938DE
Generated	2026-07-29

Product Overview

ELECTRONIC DOL STARTER 24VDC 7A

Electronic direct-on-line starter, 7A, integrated motor thermal protection, operational voltage $U_e \leq 500VAC$, auxiliary and control supply voltage 24VDC

AVVIATORE. DIRETTO ELETTR. 24VDC 7A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Electromechanical starters - LOVATO ELECTRIC

Additional Product Information

ME070FD024

Electronic direct-on-line starter, 7A, integrated motor thermal protection, operational voltage $U_e \leq 500VAC$, auxiliary and control supply voltage 24VDC

Technical specifications

Type of product:Electronic motor starterFunctions:Direct-On-Line starterSafe torque Off (STO) safety function:NoThermal protection:Integrated, class 10AIEC operating current and power I_e (AC3) 400V [A/Kw]:7Type:Electronic direct-on-line starter, 7A, integrated motor thermal protectionOrder code ME070FD024

Weight [g] 300

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 150X120X30

Volume [cm³] 540

Bar code [EAN13] 8013975320952

HS Code 85365003

177.68 £

ETIM for ME070FD024 Low-voltage industrial controls and switchgear (EC001037)

Feature Name

Feature Value

Rated control supply voltage DC (EF003980)

24 V

Overload release current setting (EF002336)

1.5 A

Ambient temperature, upper operating limit (EF009603)

50 °C

Rated operation current at AC-3, 400 V (EF009602)

7.0 A

Rated power, 460 V, 60 Hz, 3-phase (EF009600)

3 kW

Number of indicator lights (EF001965)

3

Rated operation current I_e (EF001443)

7.0 A

Number of auxiliary contacts as normally closed contact (EF001377)

2

Rated operation power at AC-3, 400 V (EF001364)

3 kW

Depth (EF000049)

140 mm

Height (EF000040)

100 mm

Width (EF000008)

22.5 mm

Temperature compensated overload protection (EF009604)

Yes

Supporting protocol for SafetyBUS p (EF007527)

No

Supporting protocol for PROFIsafe (EF007526)

No

Supporting protocol....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / ME070FD024 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.