

INDUSTRIAL COMPONENT DATA

ME070RD024 LOVATO ELECTRONIC REVERSING STARTER 24VDC 7A

Brand: LOVATO ELECTRIC | Manufacturer Part Number: ME070RD024



Manufacturer	LOVATO ELECTRIC
MPN / Reference	ME070RD024
Catalog number	ME070RD024
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-884E61BDF3
Generated	2026-07-31

Product Overview

ELECTRONIC REVERSING STARTER 24VDC 7A

Electronic reversing starter, 7A, integrated motor thermal protection, operational voltage $U_e \leq 500VAC$, auxiliary and control supply voltage 24VDC

TELEINVERTITORE ELETTRONICO 24VDC 7A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Electromechanical starters - LOVATO ELECTRIC

Additional Product Information

ME070RD024

Electronic reversing starter, 7A, integrated motor thermal protection, operational voltage $U_e \leq 500VAC$, auxiliary and control supply voltage 24VDC

Technical specifications

Type of product:Electronic motor starterFunctions:Reversing starterSafe torque Off (STO) safety function:NoThermal protection:Integrated, class 10AIEC operating current and power $I_e (AC3) 400V [A/Kw]:7$ Type:Electronic reversing starter, 7A, integrated motor thermal protectionOrder code ME070RD024

Weight [g] 300

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 150X120X30

Volume [cm³] 540

Bar code [EAN13] 8013975320976
HS Code 85365003
199.04 £
ETIM for ME070RD024 Low-voltage industrial controls and switchgear (EC001037)
Feature Name
Feature Value
Rated control supply voltage DC (EF003980)
24 V
Overload release current setting (EF002336)
1.5 A
Ambient temperature, upper operating limit (EF009603)
50 °C
Rated operation current at AC-3, 400 V (EF009602)
7.0 A
Rated power, 460 V, 60 Hz, 3-phase (EF009600)
3 kW
Number of indicator lights (EF001965)
4
Rated operation current I_e (EF001443)
7.0 A
Number of auxiliary contacts as normally closed contact (EF001377)
3
Rated operation power at AC-3, 400 V (EF001364)
3 kW
Depth (EF000049)
140 mm
Height (EF000040)
100 mm
Width (EF000008)
22.5 mm
Temperature compensated overload protection (EF009604)
Yes
Supporting protocol for SafetyBUS p (EF007527)
No
Supporting protocol for PROFIsafe (EF007526)
No
Supporting protocol for PROFINET IO...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / ME070RD024 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.