

INDUSTRIAL COMPONENT DATA

ME070RSD024 LOVATO ELECTRONIC. REV. STARTER WITH STO 24VDC 7A

Brand: LOVATO ELECTRIC | Manufacturer Part Number: ME070RSD024



Manufacturer	LOVATO ELECTRIC
MPN / Reference	ME070RSD024
Catalog number	ME070RSD024
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-404D83400D
Generated	2026-08-01

Product Overview

ELECTRONIC. REV. STARTER WITH STO 24VDC 7A

Electronic reversing starter, 7A, integrated motor thermal protection and STO (Safe Torque Off) emergency stop, operational voltage $U_e \leq 500VAC$, auxiliary and control supply voltage 24VDC

TELEINVERTIT. ELETTR. CON STO 24VDC 7A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Electromechanical starters - LOVATO ELECTRIC

Additional Product Information

ME070RSD024

Electronic reversing starter, 7A, integrated motor thermal protection and STO (Safe Torque Off) emergency stop, operational voltage $U_e \leq 500VAC$, auxiliary and control supply voltage 24VDC

Technical specifications

Type of product: Electronic motor starter
Functions: Reversing starter
Safe torque Off (STO) safety function: Built-in
Thermal protection: Integrated, class 10A IEC operating current and power $I_e (AC3) 400V [A/Kw]: 7$
Type: Electronic reversing starter, 7A, integrated motor thermal protection and STO (Safe Torque Off) emergency stop
Order code ME070RSD024

Weight [g] 300

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 150X120X30

Volume [cm³] 540

Bar code [EAN13] 8013975321010

HS Code 85365003

227.08 £

ETIM for ME070RSD024 Low-voltage industrial controls and switchgear (EC001037)

Feature Name

Feature Value

Rated control supply voltage DC (EF003980)

24 V

Overload release current setting (EF002336)

1.5 A

Ambient temperature, upper operating limit (EF009603)

50 °C

Rated operation current at AC-3, 400 V (EF009602)

7.0 A

Rated power, 460 V, 60 Hz, 3-phase (EF009600)

3 kW

Number of indicator lights (EF001965)

4

Rated operation current I_e (EF001443)

7.0 A

Number of auxiliary contacts as normally closed contact (EF001377)

3

Rated operation power at AC-3, 400 V (EF001364)

3 kW

Depth (EF000049)

140 mm

Height (EF000040)

100 mm

Width (EF000008)

22.5 mm

Temperature compensated overload protection (EF009604)

Yes

Supporting protocol for SafetyBUS p (EF007...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / ME070RSD024 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.