

INDUSTRIAL COMPONENT DATA

KMC1L20 LOVATO LIMIT SWITCH, K SERIES, ROLLER CENTRE PUSH LEVER, 1 BOTTOM CABLE ENTRY. DIMENSIONS TO EN 5004..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: KMC1L20



Manufacturer	LOVATO ELECTRIC
MPN / Reference	KMC1L20
Catalog number	10000
Category	End switch
Minimum order	1 Pcs
Document ID	EO-B7C7EBEB06
Generated	2026-08-02

Product Overview

LIMIT SWITCH, K SERIES, ROLLER CENTRE PUSH LEVER, 1 BOTTOM CABLE ENTRY. DIMENSIONS TO EN 50047, METAL BODY, CONTACTS 2NO SLOW BREAK. PLASTIC ROLLER

METAL ROLLER LEVER 2NO SLOW BREAK

Limit switch, K series, roller centre push lever, 1 bottom cable entry. Dimensions to EN 50047, metal body, contacts 2NO slow action. Plastic roller

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LOVATO ELECTRIC > Limit, micro and foot switches - LOVATO ELECTRIC
--------------	--

Additional Product Information

KMC1L20

Limit switch, K series, roller centre push lever, 1 bottom cable entry. Dimensions to EN 50047, metal body, contacts 2NO slow action. Plastic roller

Technical specifications

Type of product: Metal and plastic limit switches Product characteristics: Roller centre push lever Housing

material: Aluminium-zinc alloy Roller material: Plastic Type of contacts: 2NO Slow action Cable entry: M20 on the bottom Order code KMC1L20

Weight [g] 156

Qty. per package 1

Multiple qty. of packs per order 1
Package dimensions [mm] 100X044X032
Volume [cm³] 140.8
Bar code [EAN13] 8013975115824
HS Code 85365080
45.17 £
ETIM for KMC1L20 Sensors (EC000030)
Feature Name
Feature Value
Alignment of the control element (EF008793)
Roller cam crossed
Type of interface (EF006977)
None
Type of control element (EF006976)
Roller lever
Degree of protection (IP) (EF005474)
IP65
Construction type housing (EF004008)
Cuboid
Explosion safety category for dust (EF003998)
None
Explosion safety category for gas (EF003997)
None
Type of electric connection (EF003961)
Cable entry metrical
Type of interface for safety communication (EF003956)
None
Coating housing (EF001601)
Powder coated
Housing material (EF001596)
Metal
Switching function (EF000189)
Slow-action switch
Ambient temperature during operating (EF007515)
-25 °C
Switching function latching (EF007447)
No
Output electronic (EF006987)
No
Forced opening (EF006694)
Yes
With status indication (EF001602)
No
Suitable for safety functions (EF001597)
No
Number of contacts as c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / KMC1L20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.