

INDUSTRIAL COMPONENT DATA

KME2L03 LOVATO LIMIT SWITCH, K SERIES, ROLLER LEVER PLUNGER, 1 BOTTOM CABLE ENTRY. DIMENSIONS TO EN 50047, M..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: KME2L03



Manufacturer	LOVATO ELECTRIC
MPN / Reference	KME2L03
Catalog number	10000
Category	End switch
Minimum order	1 Pcs
Document ID	EO-55CF77C2C8
Generated	2026-08-04

Product Overview

LIMIT SWITCH, K SERIES, ROLLER LEVER PLUNGER, 1 BOTTOM CABLE ENTRY. DIMENSIONS TO EN 50047, METAL BODY, CONTACTS 3NC SLOW BREAK. METAL ROLLER
METAL ROLLER LEVER 3NC SLOW BREAK

Limit switch, K series, roller lever plunger, 1 bottom cable entry. Dimensions to EN 50047, metal body, contacts 3NC slow action. Metal roller

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LOVATO ELECTRIC > Limit, micro and foot switches - LOVATO ELECTRIC
--------------	--

Additional Product Information

KME2L03

Limit switch, K series, roller lever plunger, 1 bottom cable entry. Dimensions to EN 50047, metal body, contacts 3NC slow action. Metal roller

Technical specifications

Type of product: Metal and plastic limit switches
Product characteristics: Roller lever plunger
Housing material: Aluminium-zinc alloy
Roller material: Metal
Type of contacts: 3NC Slow action
Cable entry: M20 on the bottom
Order code KME2L03

Weight [g] 196

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 133X044X032

Volume [cm³] 187.264

Bar code [EAN13] 8013975116241

HS Code 85365080

61.19 £

ETIM for KME2L03 Sensors (EC000030)

Feature Name

Feature Value

Alignment of the control element (EF008793)

Roller cam crossed

Type of interface (EF006977)

None

Type of control element (EF006976)

Roller lever

Degree of protection (IP) (EF005474)

IP65

Construction type housing (EF004008)

Cuboid

Explosion safety category for dust (EF003998)

None

Explosion safety category for gas (EF003997)

None

Type of electric connection (EF003961)

Cable entry metrical

Type of interface for safety communication (EF003956)

None

Coating housing (EF001601)

Powder coated

Housing material (EF001596)

Metal

Switching function (EF000189)

Slow-action switch

Ambient temperature during operating (EF007515)

-25 °C

Switching function latching (EF007447)

No

Output electronic (EF006987)

No

Forced opening (EF006694)

Yes

With status indication (EF001602)

No

Suitable for safety functions (EF001597)

No

Number of contacts as change-over...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / KME2L03 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.