

INDUSTRIAL COMPONENT DATA

KBD2L12 LOVATO LIMIT SWITCH, K SERIES, ROLLER SIDE PUSH LEVER, 1 BOTTOM CABLE ENTRY. DIMENSIONS TO EN 50047,..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: KBD2L12



Manufacturer	LOVATO ELECTRIC
MPN / Reference	KBD2L12
Catalog number	10000
Category	End switch
Minimum order	1 Pcs
Document ID	EO-11AFA523E3
Generated	2026-08-05

Product Overview

LIMIT SWITCH, K SERIES, ROLLER SIDE PUSH LEVER, 1 BOTTOM CABLE ENTRY. DIMENSIONS TO EN 50047, PLASTIC BODY, CONTACTS 1NO+2NC SLOW BREAK. METAL ROLLER

METAL ROLLER SIDE LEVER 1NO+2NC SLOW

Limit switch, K series, roller side push lever, 1 bottom cable entry. Dimensions to EN 50047, plastic body, contacts 1NO+2NC slow action. Metal roller

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Limit, micro and foot switches - LOVATO ELECTRIC

Additional Product Information

KBD2L12

Limit switch, K series, roller side push lever, 1 bottom cable entry. Dimensions to EN 50047, plastic body, contacts 1NO+2NC slow action. Metal roller

Technical specifications

Type of product: Metal and plastic limit switches Product characteristics: Roller side push lever Housing material: Polymer thermoplastic Roller material: Metal Type of contacts: 1NO+2NC Slow action Cable entry: M20 on the bottom Order code KBD2L12

Weight [g] 84

Qty. per package 1

Multiple qty. of packs per order 1
Package dimensions [mm] 100X044X032
Volume [cm³] 140.8
Bar code [EAN13] 8013975114070
HS Code 85365080
48.24 £
ETIM for KBD2L12 Sensors (EC000030)
Feature Name
Feature Value
Alignment of the control element (EF008793)
Roller cam crossed
Type of interface (EF006977)
None
Type of control element (EF006976)
Roller lever
Degree of protection (IP) (EF005474)
IP65
Construction type housing (EF004008)
Cuboid
Explosion safety category for dust (EF003998)
None
Explosion safety category for gas (EF003997)
None
Type of electric connection (EF003961)
Cable entry metrical
Type of interface for safety communication (EF003956)
None
Coating housing (EF001601)
Other
Housing material (EF001596)
Plastic
Switching function (EF000189)
Slow-action switch
Ambient temperature during operating (EF007515)
-25 °C
Switching function latching (EF007447)
No
Output electronic (EF006987)
No
Forced opening (EF006694)
Yes
With status indication (EF001602)
No
Suitable for safety functions (EF001597)
No
Number of contacts as chang...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / KBD2L12 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.