

INDUSTRIAL COMPONENT DATA

KNB2L02 LOVATO Contacts 2NC slow break. Metal roller

Brand: LOVATO ELECTRIC | Manufacturer Part Number: KNB2L02



Manufacturer	LOVATO ELECTRIC
MPN / Reference	KNB2L02
Catalog number	10000
Category	End switch
Minimum order	1 Pcs
Document ID	EO-FDC72A8338
Generated	2026-08-05

Product Overview

Contacts 2NC slow break. Metal roller

METAL TOP ROLLER PLUNGER 2 ENTR L/SW 2NC

Limit switch, K series, top roller push plunger, 2 side cable entry. Dimensions compatible to EN 50047, metal body, contacts 2NC slow action. Metal roller

K SERIES LIMIT SWITCH, ROD WITH ROLLER, 2 SIDE ENTRIES FOR CABLES. EN 50047 COMPATIBLE DIMENSIONS, METAL HOUSING, SLOW 2NC CONTACTS. METAL WHEEL

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Limit, micro and foot switches - LOVATO ELECTRIC

Additional Product Information

KNB2L02

Limit switch, K series, top roller push plunger, 2 side cable entry. Dimensions compatible to EN 50047, metal body, contacts 2NC slow action. Metal roller

Technical specifications

Type of product: Metal and plastic limit switches Product characteristics: Top roller push plunger Housing

material: Aluminium-zinc alloy Roller material: Metal Type of contacts: 2NC Slow action Cable entry: M20 on the sides Order code KNB2L02

Weight [g] 220

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 065X046X090

Volume [cm³] 269.1
Bar code [EAN13] 8013975128039
HS Code 85365080
48.73 £
ETIM for KNB2L02 Sensors (EC000030)
Feature Name
Feature Value
Alignment of the control element (EF008793)
Roller cam straight
Type of interface (EF006977)
None
Type of control element (EF006976)
Roller cam
Degree of protection (IP) (EF005474)
IP65
Construction type housing (EF004008)
Cuboid
Explosion safety category for dust (EF003998)
None
Explosion safety category for gas (EF003997)
None
Type of electric connection (EF003961)
Cable entry metrical
Type of interface for safety communication (EF003956)
None
Coating housing (EF001601)
Powder coated
Housing material (EF001596)
Metal
Switching function (EF000189)
Slow-action switch
Ambient temperature during operating (EF007515)
-25 °C
Switching function latching (EF007447)
No
Output electronic (EF006987)
No
Forced opening (EF006694)
Yes
With status indication (EF001602)
No
Suitable for safety functions (EF001597)
No
Number of contacts as....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / KNB2L02 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.