

INDUSTRIAL COMPONENT DATA

P1MB1PC13 LOVATO MINIATURE CIRCUIT BREAKER, 1P 10KA. 1 MODULE, CHARACTERISTIC C, 13A

Brand: LOVATO ELECTRIC | Manufacturer Part Number: P1MB1PC13



Manufacturer	LOVATO ELECTRIC
MPN / Reference	P1MB1PC13
Catalog number	10000
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-108887DE97
Generated	2026-08-03

Product Overview

MINIATURE CIRCUIT BREAKER, 1P - 10KA. 1 MODULE, CHARACTERISTIC C, 13A

MINIATURE CIRCUIT BREAKER 1P C 13A 10KA

CIRCUIT BREAKER, 1P - 10KA. 1 MODULE, FEATURE C, 13A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Miniature and residual circuit breakers

Additional Product Information

Order code P1MB1PC13

Weight [g] 115

Package dimensions [mm] 250X100X080

Volume [cm³] 166.667

Bar code [EAN13] 8013975214268

HS Code 85362010

ETIM for P1MB1PC13 Circuit breakers and fuses (EC000042)

Feature Name

Feature Value

Degree of protection (IP) (EF005474)

IP20

Release characteristic (EF000889)

C

Voltage type (EF000187)

AC/DC

Ambient temperature during operating (EF007515)

-40 °C

Connectable conductor cross section solid-core (EF007337)

1 mm²

Frequency (EF000416)

50 Hz

Additional equipment possible (EF008148)

Yes

Flush-mounted installation (EF007517)

No

Concurrently switching neutral conductor (EF005997)

Yes

Explosion-proof (EF004663)

No

Rated impulse withstand voltage U_{imp} (EF011980)

4 kV

Rated short-circuit breaking capacity I_{cu} according to IEC 60947-2 at 400 V (EF009558)

10 kA

Rated short-circuit breaking capacity I_{cu} according to IEC 60947-2 at 230 V (EF009557)

10 kA

Rated short-circuit breaking capacity I_{cn} according to EN 60898 at 230 V (EF009556)

10 kA

Rated short-circuit breaking capacity I_{cn} according to EN 60898 at 400 V (EF009555)

10 kA

Number of poles (total) (EF008618)

1

Number of protected poles (EF005548)

1

Width in number of modular spacings (EF002950)

1

Pollution degree (EF002570)

2

Over voltage category (EF002569)

3

Rated insulation voltage U_i (EF001366)

1000 V

Rated voltage (EF000228)

230 V

Rated current (EF000227)

13 A

Built-in depth (EF000218)

66 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / P1MB1PC13 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.