

INDUSTRIAL COMPONENT DATA

11BGP09T4A024 BGP09T4A024 LOVATO FOUR-POLE CONTACTOR, AC COIL 50/60HZ, 24VAC, REAR PCB SOLDER PIN

Brand: LOVATO ELECTRIC | Manufacturer Part Number: 11BGP09T4A024



Manufacturer	LOVATO ELECTRIC
MPN / Reference	11BGP09T4A024
Catalog number	BGP09T4A024
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-BB77FD192A
Generated	2026-08-06

Product Overview

FOUR-POLE CONTACTOR, AC COIL 50/60HZ, 24VAC, REAR PCB SOLDER PIN

Minicont. 4P 20A AC1 24V 50/60Hz Printed Circuit Board

Four-pole contactor, AC coil 50/60Hz, 24VAC, rear PCB solder pin

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Industrial Contactors and Accessories - LOVATO ELECTRIC

Additional Product Information

11BGP09T4A024

Four-pole contactor, AC coil 50/60Hz, 24VAC, rear PCB solder pin

Technical specifications

Type of product:ContactorsNumber of poles:4Type of coil:AC coil 50/60HzRated coil voltage [V]:24IEC operating current I_{th} (AC1) [A]:20IEC operating current and power I_e (AC3) 400V [A/Kw]:9A / 4.0KwUL/CSA horsepower ratings 480V [HP]:5Type of mounting:Screw / DIN rail 35mmOrder code 11BGP09T4A024

Weight [g] 198

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 060X045X070

Volume [cm³] 189

Bar code [EAN13] 8013975145203

HS Code 85365080

51.15 £

ETIM for 11BGP09T4A024 Low-voltage industrial controls and switchgear (EC000066)

Feature Name

Feature Value

Voltage type for actuating (EF008242)

AC

Type of electrical connection of main circuit (EF006819)

PCB connection

Rated control supply voltage AC 60 Hz (EF003979)

24 V

Rated control supply voltage AC 50 Hz (EF003978)

24 V

Modular version (EF001126)

No

Rated operation current I_e at AC-4, 400 V (EF008495)

4 A

Rated operation current I_e at AC-1, 400 V (EF001393)

20 A

Rated operation current I_e at AC-3, 400 V (EF001392)

9 A

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of normally closed contacts as main contact (EF001375)

0

Number of normally open contacts as main contact (EF001374)

4

Rated operation power at AC-3, 400 V (EF001364)

4 kW

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / 11BGP09T4A024 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.