

INDUSTRIAL COMPONENT DATA

RM148 LOVATO EARTH LEAKAGE RELAY WITH 1 OPERATION THRESHOLD, MODULAR, 35MM DIN (IEC/EN 60715) RAIL MOUNTING...

Brand: LOVATO ELECTRIC | Manufacturer Part Number: RM148



Manufacturer	LOVATO ELECTRIC
MPN / Reference	RM148
Catalog number	10000
Category	Residual current monitoring relay
Minimum order	1 Pcs
Document ID	EO-8D73C76A8A
Generated	2026-08-04

Product Overview

EARTH LEAKAGE RELAY WITH 1 OPERATION THRESHOLD, MODULAR, 35MM DIN (IEC/EN 60715) RAIL MOUNTING. EXTERNAL CT. FIXED TRIPPING SET POINT AND TIME, 24-48VAC/DC
MOD EARTH LEAKAGE RELAY 24-48VAC/DC

Earth leakage relay with 1 operatin threshold, modular, 35mm DIN (IEC/EN60715) rail mounting. External CT. Fixed tripping set point and time, 24-48VAC/DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LOVATO ELECTRIC > Earth leakage relays - LOVATO ELECTRIC
--------------	--

Additional Product Information

RM148

Earth leakage relay with 1 operatin threshold, modular, 35mm DIN (IEC/EN60715) rail mounting. External CT. Fixed tripping set point and time, 24-48VAC/DC

Technical specifications

Type of product:Earth leakage relaysResidual operation characteristic:Type AType of installation:Modular DIN rail mountingToroidal transformer:ExternalN° of operating threshold:1Rated supply voltage:24-48VAC/DCOrder code RM148
Weight [g] 170

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 115X120X065

Volume [cm³] 897

Bar code [EAN13] 8013975111079

HS Code 85389091

262.22 £

ETIM for RM148 Relays (EC001445)

Feature Name

Feature Value

Type of electric connection (EF003961)

Screw connection

Function (EF000030)

For AC-current system

Response value amperage 1 (EF008204)

25 mA

Indication of difference current (EF003424)

Yes

Error registration possible (EF003423)

Yes

With detachable clamps (EF003340)

No

Number of contacts as change-over contact (EF008257)

1

Number of contacts as normally open contact (EF008256)

0

Number of contacts as normally closed contact (EF008255)

0

Min. adjustable delay-on energization time (EF008190)

0.02 s

Max. permitted delay-on energization time (EF008189)

5 s

Depth (EF000049)

67 mm

Height (EF000040)

89 mm

Width (EF000008)

52 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / RM148 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.