

INDUSTRIAL COMPONENT DATA

PMF20A240 LOVATO FREQUENCY MONITORING RELAY FOR SINGLE AND THREE-PHASE SYSTEMS, MINIMUM AND MAXIMUM FREQUENC..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: PMF20A240



Manufacturer	LOVATO ELECTRIC
MPN / Reference	PMF20A240
Catalog number	10000
Category	Frequency monitoring relay
Minimum order	1 Pcs
Document ID	EO-8F8991AF0B
Generated	2026-07-29

Product Overview

FREQUENCY MONITORING RELAY FOR SINGLE AND THREE-PHASE SYSTEMS, MINIMUM AND MAXIMUM FREQUENCY, 220...240VAC 50/60HZ

MULTIFUNCTION FREQUENCY PROTECTION RELAY

Frequency monitoring relay for single and three-phase systems, minimum and maximum frequency, 220...240VAC 50/60Hz
FREQUENCY RELAY FOR SINGLE-PHASE AND THREE-PHASE SYSTEMS, MINIMUM AND MAXIMUM FREQUENCY, 220...240VAC 50/60HZ

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LOVATO ELECTRIC > Protection relays - LOVATO ELECTRIC
--------------	---

Additional Product Information

PMF20A240

Frequency monitoring relay for single and three-phase systems, minimum and maximum frequency, 220...240VAC 50/60Hz

Technical specifications

Type of product: Frequency monitoring relays
Type of system: Single-phase
Number of relay outputs: 1
Rated supply voltage: Self powered
Programming mode: Potentiometers
Order code PMF20A240

Weight [g] 126

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 095X040X075

Volume [cm³] 285

Bar code [EAN13] 8013975142271

HS Code 85364900

513.12 £

ETIM for PMF20A240 Relays (EC001442)

Feature Name

Feature Value

Type of electric connection (EF003961)

Screw connection

Response value for frequency (EF003417)

45 Hz

With detachable clamps (EF003340)

No

Number of contacts as change-over contact (EF008257)

1

Number of contacts as normally open contact (EF008256)

0

Number of contacts as normally closed contact (EF008255)

0

Min. adjustable off-delay time (EF008192)

0.1 s

Max. permitted off-delay time (EF008191)

20 s

Min. adjustable delay-on energization time (EF008190)

0.1 s

Max. permitted delay-on energization time (EF008189)

20 s

Depth (EF000049)

64.9 mm

Height (EF000040)

104.7 mm

Width (EF000008)

35.8 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / PMF20A240 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.