

INDUSTRIAL COMPONENT DATA

KPM2S11 LOVATO PREWIRED METAL LIMIT SWITCH, K SERIES, WOBBLE STICK, OMNIDIRECTIONAL, CONTACTS 1NO+1NC SNAP A..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: KPM2S11



Manufacturer	LOVATO ELECTRIC
MPN / Reference	KPM2S11
Catalog number	10000
Category	End switch
Minimum order	1 Pcs
Document ID	EO-1A7067139D
Generated	2026-08-05

Product Overview

PREWIRED METAL LIMIT SWITCH, K SERIES, WOBBLE STICK, OMNIDIRECTIONAL, CONTACTS 1NO+1NC SNAP ACTION

OMNIDIR WOBBLE STICK PREW METAL 1NO+1NC

Prewired with 2m long cable metal limit switch, K series, wobble stick, omnidirectional. Contacts 1NO+1NC snap action
K SERIES PRE-WIRED METAL LIMIT SWITCH, OMNIDIRECTIONAL ROD, SNAP-IN 1NO+1NC CONTACTS

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LOVATO ELECTRIC > Limit, micro and foot switches - LOVATO ELECTRIC
--------------	--

Additional Product Information

KPM2S11

Prewired with 2m long cable metal limit switch, K series, wobble stick, omnidirectional. Contacts 1NO+1NC snap action
Technical specifications

Type of product:Prewired metal limit switchesProduct characteristics:Omnidirectional wobble stickHousing material:Aluminium-zinc alloyRoller material:MetalType of contacts:1NO+1NC Snap actionOrder code KPM2S11

Weight [g] 298

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 325X220X015

Volume [cm³] 1072.5
Bar code [EAN13] 8013975150290
HS Code 85365080
77.57 £
ETIM for KPM2S11 Sensors (EC000030)
Feature Name
Feature Value
Alignment of the control element (EF008793)
Other
Type of interface (EF006977)
None
Type of control element (EF006976)
Spring-rod
Degree of protection (IP) (EF005474)
IP67
Construction type housing (EF004008)
Cuboid
Explosion safety category for dust (EF003998)
None
Explosion safety category for gas (EF003997)
None
Type of electric connection (EF003961)
With cable preassembled
Type of interface for safety communication (EF003956)
None
Coating housing (EF001601)
Powder coated
Housing material (EF001596)
Metal
Switching function (EF000189)
Quick-break switch
Ambient temperature during operating (EF007515)
-25 °C
Switching function latching (EF007447)
No
Output electronic (EF006987)
No
Forced opening (EF006694)
Yes
With status indication (EF001602)
No
Suitable for safety functions (EF001597)
No
Number of contacts as change-over contact (EF008257)
0
Number of contacts as normally open....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / KPM2S11 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.