

INDUSTRIAL COMPONENT DATA**P1MB3PD08 LOVATO Circuit breaker D Curve 3 Pole 8A 10 kA**

Brand: LOVATO ELECTRIC | Manufacturer Part Number: P1MB3PD08



Manufacturer	LOVATO ELECTRIC
MPN / Reference	P1MB3PD08
Catalog number	10000
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-9F84E64642
Generated	2026-08-02

Product Overview

Circuit breaker D Curve 3 Pole 8A 10 kA
MINIATURE CIRCUIT BREAKER 3P D 8A 10KA
Miniature circuit breaker, 3P - 10kA. 3 modules, characteristic D, 8A

STRUCTURED PRODUCT DATA**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LOVATO ELECTRIC > Miniature and residual circuit breakers
--------------	---

Additional Product Information

P1MB3PD08
Miniature circuit breaker, 3P - 10kA. 3 modules, characteristic D, 8A
Technical specifications
Type of product:Miniature circuit breakersNumber of DIN modules:3Number of poles:3PTripping curve:DRated current In [A]:8Compliance:IEC / UL1077Order code P1MB3PD08
Weight [g] 345
Qty. per package 4
Multiple qty. of packs per order 4
Package dimensions [mm] 250X100X080
Volume [cm³] 500
Bar code [EAN13] 8013975237601
HS Code 85362010
ETIM for P1MB3PD08 Circuit breakers and fuses (EC000042)
Feature Name

Feature Value

Degree of protection (IP) (EF005474)

IP20

Release characteristic (EF000889)

D

Voltage type (EF000187)

AC

Ambient temperature during operating (EF007515)

-40 °C

Connectable conductor cross section solid-core (EF007337)

1 mm²

Frequency (EF000416)

50 Hz

Additional equipment possible (EF008148)

Yes

Flush-mounted installation (EF007517)

No

Concurrently switching neutral conductor (EF005997)

Yes

Explosion-proof (EF004663)

No

Rated impulse withstand voltage Uimp (EF011980)

4 kV

Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 400 V (EF009558)

10 kA

Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 230 V (EF009557)

10 kA

Rated short-circuit breaking capacity Icn according to EN 60898 at 230 V (EF009556)

10 kA

Rated short-circuit breaking capacity Icn according to EN 60898 at 400 V (EF009555)

10 kA

Number of poles (total) (EF008618)

3

Number of protected poles (EF005548)

3

Width in number of modular spacings (EF002950)

3

Pollutio...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / P1MB3PD08 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.