

## INDUSTRIAL COMPONENT DATA

# P1RC4P63B300 LOVATO RESIDUAL CURRENT OPERATED CIRCUIT BREAKER, 4 MODULES, 4P TYPE B, 63A, 300mA

Brand: LOVATO ELECTRIC | Manufacturer Part Number: P1RC4P63B300



|                 |                                         |
|-----------------|-----------------------------------------|
| Manufacturer    | LOVATO ELECTRIC                         |
| MPN / Reference | P1RC4P63B300                            |
| Catalog number  | 10000                                   |
| Category        | Residual current circuit breaker (RCCB) |
| Minimum order   | 1 Pcs                                   |
| Document ID     | EO-2C80BF52EE                           |
| Generated       | 2026-08-05                              |

## Product Overview

RESIDUAL CURRENT OPERATED CIRCUIT BREAKER, 4 MODULES, 4P - TYPE B, 63A, 300mA

RESIDUAL CURRENT DEVICE 4P 63A IDN 300MA

Residual current operated circuit breaker, 4 modules, 4P - type B, 63A, 300mA

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path LOVATO ELECTRIC &gt; Miniature and residual circuit breakers

## Additional Product Information

P1RC4P63B300

Residual current operated circuit breaker, 4 modules, 4P - type B, 63A, 300mA

Technical specifications

Type of product:Residual current operated circuit breakersNumber of DIN modules:4Number of poles:4PResidual operation characteristic:BRated residual current I<sub>n</sub> [mA]:300Rated current I<sub>n</sub> [A]:63Compliance:IECOrder code P1RC4P63B300

Weight [g] 335

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 087X073X075

Volume [cm<sup>3</sup>] 476.325

Bar code [EAN13] 8013975222607

HS Code 85363030

ETIM for P1RC4P63B300 Circuit breakers and fuses (EC000003)

|                                                               |  |
|---------------------------------------------------------------|--|
| Feature Name                                                  |  |
| Feature Value                                                 |  |
| Degree of protection (IP) (EF005474)                          |  |
| IP20                                                          |  |
| Frequency (EF005455)                                          |  |
| 50/60 Hz                                                      |  |
| Leakage current type (EF002560)                               |  |
| B                                                             |  |
| Voltage type (EF000187)                                       |  |
| AC                                                            |  |
| Mounting method (EF000003)                                    |  |
| DIN rail                                                      |  |
| Ambient temperature during operating (EF007515)               |  |
| -25 °C                                                        |  |
| Connectable conductor cross section solid-core (EF007337)     |  |
| 2.5 mm <sup>2</sup>                                           |  |
| Additional equipment possible (EF008148)                      |  |
| No                                                            |  |
| With interlocking device (EF007385)                           |  |
| No                                                            |  |
| Explosion-proof (EF004663)                                    |  |
| No                                                            |  |
| Short-time delayed tripping (EF003604)                        |  |
| No                                                            |  |
| Selective protection (EF002561)                               |  |
| No                                                            |  |
| Rated impulse withstand voltage U <sub>imp</sub> (EF011980)   |  |
| 4 kV                                                          |  |
| Width in number of modular spacings (EF002950)                |  |
| 4                                                             |  |
| Pollution degree (EF002570)                                   |  |
| 2                                                             |  |
| Short-circuit breaking capacity (I <sub>cw</sub> ) (EF002562) |  |
| 10 kA                                                         |  |
| Rated fault current (EF002358)                                |  |
| 10 A                                                          |  |
| Number of poles (EF001391)                                    |  |
| 4                                                             |  |
| Rated insulation voltage U <sub>i</sub> (EF001366)            |  |
| 400 V                                                         |  |
| Rated voltage (EF000228)                                      |  |
| 400 V                                                         |  |
| Rated current (EF000227)                                      |  |
| 63 A                                                          |  |
| Built-in depth (EF000218)                                     |  |
| 66 mm                                                         |  |

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / P1RC4P63B300 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.