

INDUSTRIAL COMPONENT DATA

PMA50A240 LOVATO PUMP PROTECTION RELAY FOR SINGLE AND THREE-PHASE SYSTEMS, MAXIMUM AC CURRENT AND MINIMUM CO..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: PMA50A240



Manufacturer	LOVATO ELECTRIC
MPN / Reference	PMA50A240
Catalog number	10000
Category	Current monitoring relay
Minimum order	1 Pcs
Document ID	EO-2A2F31A9A7
Generated	2026-08-05

Product Overview

PUMP PROTECTION RELAY FOR SINGLE AND THREE-PHASE SYSTEMS, MAXIMUM AC CURRENT AND MINIMUM COS?. PHASE LOSS AND INCORRECT PHASE SEQUENCE, 5A OR 16A

PUMP PROTECTION RELAY 220-240VAC

Pump protection relay for single and three-phase systems, maximum AC current and minimum COS?. Phase loss and incorrect phase sequence, 5A or 16A

PUMP PROTECTION RELAY FOR SINGLE-PHASE AND THREE-PHASE SYSTEMS, MAXIMUM AC CURRENT AND MINIMUM COS. PHASE ABSENCE AND INCORRECT SEQUENCE OF PHASES, 5TH OR 16TH

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LOVATO ELECTRIC > Protection relays - LOVATO ELECTRIC
--------------	---

Additional Product Information

PMA50A240

Pump protection relay for single and three-phase systems, maximum AC current and minimum COS?. Phase loss and incorrect phase sequence, 5A or 16A

Technical specifications

Type of product: Pump protection relays
Type of system: Single-phase and three-phase
Number of relay outputs: 1
Rated supply voltage: 220...240VAC
Rated current Ie [A]: 5 or 16
Programming mode: Potentiometers
Order code PMA50A240
Weight [g] 280

Qty. per package 1
Multiple qty. of packs per order 1
Package dimensions [mm] 095X055X075
Volume [cm³] 391.875
Bar code [EAN13] 8013975172841
HS Code 85364900
315.04 £
ETIM for PMA50A240 Relays (EC001440)
Feature Name
Feature Value
Type of electric connection (EF003961)
Screw connection
Current measuring range (EF000417)
0.1 A
Function DC-current hysteresis (EF003411)
No
Contains function DC-voltage overcurrent (EF003410)
Yes
Contains function DC-voltage under current (EF003409)
No
Three-phase overcurrent possible (EF003408)
No
Single-phase overcurrent possible (EF003407)
Yes
Three-phase under current possible (EF003406)
No
Single-phase under current possible (EF003405)
No
Three-phase hysteresis possible (EF003395)
No
Single-phase hysteresis possible (EF003394)
Yes
With detachable clamps (EF003340)
No
External current transformer (EF001923)
Yes
Number of contacts as change-over contact (EF008257)
1
Number of contacts as normally open contact (EF008256)
0
Number of contacts as normally closed contact (EF008255)
0
Min. adjustable off-delay time (EF008192)
0.1 s
Max. per...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / PMA50A240 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.