

INDUSTRIAL COMPONENT DATA

GX2092U47 LOVATO ROTARY CAM SWITCHE, GX SERIES, U47 VERSION FRONT SNAP ON MOUNT WITH HANDLE OPERATION, FOR 2..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: GX2092U47



Manufacturer	LOVATO ELECTRIC
MPN / Reference	GX2092U47
Catalog number	10000
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-14D3F3E892
Generated	2026-08-03

Product Overview

ROTARY CAM SWITCHE, GX SERIES, U47 VERSION FRONT SNAP ON MOUNT WITH HANDLE OPERATION, FOR 22MM FIXING. ON/OFF SWITCH, FOUR-POLE - 2 WAFERS - SCHEME 92

4P 2POS SWITCH FRONT MOUNTING 48X48

Rotary cam switch GX series, ON-OFF switch 4 poles 20A, for snap on front mounting with black handle for hole Ø22mm fixing, front plate 48X48mm

ROTARY CAM SWITCH GX SERIES, ON-OFF SWITCH 4 POLES 20A, FOR SNAP ON FRONT MOUNTING WITH BLACK HANDLE FOR HOLE DIAM. 22MM FINXING, FRONT PLATE 48X48MM

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LOVATO ELECTRIC > Rotary cam switches - LOVATO ELECTRIC
--------------	---

Additional Product Information

GX2092U47

Rotary cam switch GX series, ON-OFF switch 4 poles 20A, for snap on front mounting with black handle for hole Ø22mm fixing, front plate 48X48mm

Technical specifications

Type of product:ON/OFF switchesSwitching diagram:92 - ON/OFF switch 4 polesIEC Conventional free air thermal current Ith [A]:20Mounting form:U47 - Snap on fron mounting with black handle for hole diam. 22mm finxingSeries:GX - square-shaped contact blockOrder code GX2092U47

Weight [g] 144
Qty. per package 1
Multiple qty. of packs per order 1
Package dimensions [mm] 050X068X082
Volume [cm³] 278.8
Bar code [EAN13] 8013975217085
HS Code 85365080
ETIM for GX2092U47 Low-voltage industrial controls and switchgear (EC001105)
Feature Name
Feature Value
Type of control element (EF006976)
Short thumb-grip
Type of electrical connection of main circuit (EF006819)
Screw connection
Degree of protection (IP), front side (EF003118)
IP65
Housing material (EF001596)
Plastic
Model (EF000010)
On/Off switch
Complete device in housing (EF007317)
Yes
Suitable for intermediate mounting (EF007264)
No
Suitable for distribution board installation (EF007262)
Yes
Suitable for front mounting (EF007246)
Yes
Suitable for floor mounting (EF007243)
No
With retraction in 0-position (EF002428)
No
With zero (off) position (EF001416)
Yes
Number of poles (EF001391)
4
Rated permanent current I_u (EF001389)
20 A
Rated operation power at AC-3, 400 V (EF001364)
5.5 kW

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / GX2092U47 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.