

INDUSTRIAL COMPONENT DATA

KME3L20 LOVATO LIMIT SWITCH, K SERIES, ROLLER LEVER PLUNGER, 1 BOTTOM CABLE ENTRY. DIMENSIONS TO EN 50047, M..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: KME3L20



Manufacturer	LOVATO ELECTRIC
MPN / Reference	KME3L20
Catalog number	10000
Category	End switch
Minimum order	1 Pcs
Document ID	EO-767615D6A9
Generated	2026-08-03

Product Overview

LIMIT SWITCH, K SERIES, ROLLER LEVER PLUNGER, 1 BOTTOM CABLE ENTRY. DIMENSIONS TO EN 50047, METAL BODY, CONTACTS 2NO SLOW BREAK. RUBBER ROLLER

RUBBER ROLLER LEVER PLUNGER 2NO SLOW

Limit switch, K series, roller lever plunger, 1 bottom cable entry. Dimensions to EN 50047, metal body, contacts 2NO slow action. Rubber roller

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Limit, micro and foot switches - LOVATO ELECTRIC

Additional Product Information

KME3L20

Limit switch, K series, roller lever plunger, 1 bottom cable entry. Dimensions to EN 50047, metal body, contacts 2NO slow action. Rubber roller

Technical specifications

Type of product: Metal and plastic limit switches Product characteristics: Roller lever plunger Housing material: Aluminium-zinc alloy Roller material: Rubber Type of contacts: 2NO Slow action Cable entry: M20 on the bottom Order code KME3L20

Weight [g] 206

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 144X050X070

Volume [cm³] 504

Bar code [EAN13] 8013975116364

HS Code 85365080

53.59 £

ETIM for KME3L20 Sensors (EC000030)

Feature Name

Feature Value

Alignment of the control element (EF008793)

Roller cam crossed

Type of interface (EF006977)

None

Type of control element (EF006976)

Roller lever

Degree of protection (IP) (EF005474)

IP65

Construction type housing (EF004008)

Cuboid

Explosion safety category for dust (EF003998)

None

Explosion safety category for gas (EF003997)

None

Type of electric connection (EF003961)

Cable entry metrical

Type of interface for safety communication (EF003956)

None

Coating housing (EF001601)

Powder coated

Housing material (EF001596)

Metal

Switching function (EF000189)

Slow-action switch

Ambient temperature during operating (EF007515)

-25 °C

Switching function latching (EF007447)

No

Output electronic (EF006987)

No

Forced opening (EF006694)

Yes

With status indication (EF001602)

No

Suitable for safety functions (EF001597)

No

Number of contacts as change-over c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / KME3L20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.