

INDUSTRIAL COMPONENT DATA

M3P01270230 LOVATO STAR-DELTA STARTER, ENCLOSED STARTERS, WITH START AND STOP/RESET BUTTONS. STARTING TIME U..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: M3P01270230



Manufacturer	LOVATO ELECTRIC
MPN / Reference	M3P01270230
Catalog number	10000
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-966B576EA6
Generated	2026-08-06

Product Overview

STAR-DELTA STARTER, ENCLOSED STARTERS, WITH START AND STOP/RESET BUTTONS. STARTING TIME UP TO 12 SECONDS AND A MAXMUM OF 30 OPERATIONS /HOUR, MAX IEC OPERATING CURRENT 22A. COIL VOLTAGE 230VAC 50/60HZ

S-D-S- 22A 230V 50/60HZ W/ENCLOSURE

Star-delta starter, enclosed starter, with START and STOP/RESET buttons. Starting time up to 12 seconds and a maximum of 30 operations/hour, max IEC operating current 22A. Coil voltage 230VAC 50/60Hz

STAR-DELTA STARTER, IN INSULATED CASE, WITH START AND STOP/RESET BUTTONS. START-UP TIMES UP TO 12 SEC. AND A MAXIMUM OF 30 MANOEUVRES/HOUR, MAXIMUM OPERATING CURRENT 22A. COIL VOLTAGE 230VAC 50/60HZ

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Electromechanical starters - LOVATO ELECTRIC

Additional Product Information

M3P01270230

Star-delta starter, enclosed starter, with START and STOP/RESET buttons. Starting time up to 12 seconds and a maximum of 30 operations/hour, max IEC operating current 22A. Coil voltage 230VAC 50/60Hz

Technical specifications

Type of product:Star-delta startersUL/CSA horsepower ratings 480V [HP]:10Type:Enclosed startersType of coil:AC coilType

of pushbutton: With Start-Stop/Reset buttons Contactor coil voltage: 230VAC 50/60HZ Order code M3P01270230

Weight [g] 3480

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 295X240X225

Volume [cm³] 15930

Bar code [EAN13] 8013975182680

HS Code 85371098

965.43 £

ETIM for M3P01270230 Low-voltage industrial controls and switchgear (EC001037)

Feature Name

Feature Value

Degree of protection (NEMA) (EF011959)

4X

Type of motor starter (EF009598)

Star-delta starter

Voltage type for actuating (EF008242)

AC

Type of electrical connection for auxiliary- and control current circuit (EF006979)

Screw connection

Type of electrical connection of main circuit (EF006819)

Screw connection

Release class (EF006668)

CLASS 10 A

Degree of protection (IP) (EF005474)

IP65

Rated control supply voltage AC 60 Hz (EF003979)

230 V

Rated control supply voltage AC 50 Hz (EF003978)

230 V

Temperature compensated overload protection (EF009604)

Yes

Supporting protocol for SafetyBUS p (EF007527)

No

Supporting protocol for PROFIsafe (EF007526)

No

Supporting protocol for PROFINET IO (EF007525)

No

Supporting protocol for PROFINET CBA (EF007524...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / M3P01270230 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.