

INDUSTRIAL COMPONENT DATA

SA0B1PA320R LOVATO SURGE PROTECTION DEVICE TYPE 1 AND 2 MONOBLOCK, IEC IMPULSE CURRENT IIMP (10/350?S) 12.5k..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: SA0B1PA320R



Manufacturer	LOVATO ELECTRIC
MPN / Reference	SA0B1PA320R
Catalog number	10000
Category	Combined arrester for power supply systems
Minimum order	1 Pcs
Document ID	EO-A8056ACF86
Generated	2026-08-05

Product Overview

SURGE PROTECTION DEVICE TYPE 1 AND 2 MONOBLOCK, IEC IMPULSE CURRENT IIMP (10/350?S) 12.5kA PER POLE, 1P. WITH CONTACT REMOTE

SURGE PROTECTION DEVICE TYPE 1-2 1P

Surge protection device type 1 and 2 monoblock, IEC impulse current Iimp (10/350us) 12.5kA per pole, 1P. With remote contact

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LOVATO ELECTRIC > Surge protection devices - LOVATO ELECTRIC
--------------	--

Additional Product Information

SA0B1PA320R

Surge protection device type 1 and 2 monoblock, IEC impulse current Iimp (10/350us) 12.5kA per pole, 1P. With remote contact

Technical specifications

Type of product:SPDType of system:230/400VACType / Class:1, 2Number of poles:1PIimp [kA]:12.5In [kA]:20/50Short circuit rated current Isccr [kA]:25Type of mounting:Din railOrder code SA0B1PA320R

Weight [g] 207

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 109X023X078

Volume [cm³] 195.574

Bar code [EAN13] 8013975233900

HS Code 85365080

ETIM for SA0B1PA320R Earthing, lightning and surge protection (EC001457)

Feature Name

Feature Value

Degree of protection (IP) (EF005474)

IP20

Signalling at the device (EF004241)

Optic

Test class (EF004228)

Type 1 + 2

Construction size (EF002566)

1 modular spacing

Mounting method (EF000003)

DIN rail (top hat rail) 35 mm

Overcurrent protected voltage tapping (EF016004)

No

Voltage switching spark gap technology (EF016003)

No

System configuration TN-C-S (EF009933)

No

System configuration other (EF009932)

No

System configuration TT (EF009931)

Yes

System configuration TN-S (EF009930)

Yes

System configuration TN-C (EF009929)

Yes

System configuration TN (EF009928)

No

System configuration IT (EF009927)

No

System configuration DC (EF009926)

No

Energy-coordinated protection effect with regard to the terminal equipment (EF009798)

Yes

Integrated backup fuse (EF008797)

No

Remote signalling (EF004192)

Yes

Max. overcurrent protection device, series connection (fuse) (EF...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / SA0B1PA320R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.