

INDUSTRIAL COMPONENT DATA

SA31NA275ML LOVATO SURGE PROTECTION DEVICE TYPE 3, COMPACT VERSION, COMBINATION WAVE Uoc/Icw (1.2/50 us, 8/2..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: SA31NA275ML



Manufacturer	LOVATO ELECTRIC
MPN / Reference	SA31NA275ML
Catalog number	10000
Category	Surge protection device for terminal equipment
Minimum order	1 Pcs
Document ID	EO-FFEB5585D4
Generated	2026-08-02

Product Overview

SURGE PROTECTION DEVICE TYPE 3, COMPACT VERSION, COMBINATION WAVE Uoc/Icw (1.2/50 us, 8/20us)

6kV/3kA, 1P+N, WITH LED SIGNALING

SURGE PROTECTION DEVICE MINI TYPE 3 1P+N

Surge protection device type 3, compact version, combination wave Uoc/Icw (1.2/50 us, 8/20us) 6kV/3kA, 1P+N, with LED signaling

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Surge protection devices - LOVATO ELECTRIC

Additional Product Information

SA31NA275ML

Surge protection device type 3, compact version, combination wave Uoc/Icw (1.2/50 us, 8/20us) 6kV/3kA, 1P+N, with LED signaling

Technical specifications

Type of product:SPDType of system:230/400VACType / Class:3Number of poles:1P+NIntervention signaling:OpticalType of mounting:Parallel on socketOrder code SA31NA275ML

Weight [g] 40

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 110X075X025

Volume [cm³] 206.25

Bar code [EAN13] 8013975231050

HS Code 85365080

63.47 £

ETIM for SA31NA275ML Earthing, lightning and surge protection (EC000942)

Feature Name

Feature Value

Degree of protection (IP) (EF005474)

IP20

Signalling at the device (EF004241)

Optic

Mounting method (EF000003)

Wall socket

With interference suppressor filter (EF006025)

No

Category type 3 (EF004231)

Yes

With remote signalling contact (EF000422)

No

Max. overcurrent protection device, series connection (fuse) (EF015963)

1 A

Max. overcurrent protection device, parallel connection (fuse) (EF015962)

1 A

Max. conductor cross section flexible (fine-strand) (EF008828)

1 mm²

Max. conductor cross section solid (solid, stranded) (EF008827)

1 mm²

Voltage protection level L-PE/N-PE (EF004237)

1700 kV

Voltage protection level L-N (EF004236)

1500 kV

Nominal voltage AC (EF004220)

230 V

Max. continuous voltage AC (EF004198)

275 V

Voltage protection level (EF003525)

1500 kV

Number of poles (EF001391)

2

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / SA31NA275ML with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.