

INDUSTRIAL COMPONENT DATA

SA31NA275MS LOVATO SURGE PROTECTION DEVICE TYPE 3, COMPACT VERSION, COMBINATION WAVE Uoc/Icw (1.2/50 us, 8/2..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: SA31NA275MS



Manufacturer	LOVATO ELECTRIC
MPN / Reference	SA31NA275MS
Catalog number	10000
Category	Surge protection device for terminal equipment
Minimum order	1 Pcs
Document ID	EO-6BC7022EBE
Generated	2026-08-04

Product Overview

SURGE PROTECTION DEVICE TYPE 3, COMPACT VERSION, COMBINATION WAVE Uoc/Icw (1.2/50 us, 8/20us)

6kV/3kA, 1P+N, WITH SOUND SIGNALING

SURGE PROTECTION DEVICE MINI TYPE 3 1P+N

Surge protection device type 3, compact version, combination wave Uoc/Icw (1.2/50 us, 8/20us) 6kV/3kA, 1P+N, with sound signaling

TYPE 3 SURGE ARRESTER, SMALL FOOTPRINT, COMBINED IMPULSE VOLTAGE Uoc/Icw (1.2/50 ?s, 8/20?s)

6kV/3kA, 1P+N, ACOUSTIC TRIP SIGNALING

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LOVATO ELECTRIC > Surge protection devices - LOVATO ELECTRIC
--------------	--

Additional Product Information

SA31NA275MS

Surge protection device type 3, compact version, combination wave Uoc/Icw (1.2/50 us, 8/20us) 6kV/3kA, 1P+N, with sound signaling

Technical specifications

Type of product:SPDType of system:230/400VACType / Class:3Number of poles:1P+NIntervention signaling:AcousticType

of mounting:Parallel on socketOrder code SA31NA275MS

Weight [g] 20

Qty. per package 1
Multiple qty. of packs per order 1
Package dimensions [mm] 305X115X085
Volume [cm³] 99.379
Bar code [EAN13] 8013975231043
HS Code 85365080
55.87 £
ETIM for SA31NA275MS Earthing, lightning and surge protection (EC000942)
Feature Name
Feature Value
Degree of protection (IP) (EF005474)
IP20
Signalling at the device (EF004241)
Acoustic
Mounting method (EF000003)
Wall socket
With interference suppressor filter (EF006025)
No
Category type 3 (EF004231)
Yes
With remote signalling contact (EF000422)
No
Max. overcurrent protection device, series connection (fuse) (EF015963)
1 A
Max. overcurrent protection device, parallel connection (fuse) (EF015962)
1 A
Max. conductor cross section flexible (fine-strand) (EF008828)
1 mm²
Max. conductor cross section solid (solid, stranded) (EF008827)
1 mm²
Voltage protection level L-PE/N-PE (EF004237)
1700 kV
Voltage protection level L-N (EF004236)
1500 kV
Nominal voltage AC (EF004220)
230 V
Max. continuous voltage AC (EF004198)
275 V
Voltage protection level (EF003525)
1500 kV
Number of poles (EF001391)
2

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / SA31NA275MS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.