

INDUSTRIAL COMPONENT DATA

SA31NA320R LOVATO SURGE PROTECTION DEVICE TYPE 3, WITH PLUG-IN CARTRIDGE, COMBINATION WAVE Uoc/lcw (1.2/50 u..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: SA31NA320R



Manufacturer	LOVATO ELECTRIC
MPN / Reference	SA31NA320R
Catalog number	10000
Category	Surge protection device for terminal equipment
Minimum order	1 Pcs
Document ID	EO-C2343F0200
Generated	2026-08-06

Product Overview

SURGE PROTECTION DEVICE TYPE 3, WITH PLUG-IN CARTRIDGE, COMBINATION WAVE Uoc/lcw (1.2/50 us, 8/20us) 10kV/5kA, 1P+N, WITH CONTACT REMOTE

SURGE PROTECTION DEVICE TYPE 3 1P+N+R.C

Surge protection device type 3, with plug-in cartridge, combination wave Uoc/lcw (1.2/50 us, 8/20us) 10kV/5kA, 1P+N, with remote contact

TYPE 3 SURGE ARRESTER, REMOVABLE CARTRIDGE, COMBINED IMPULSE VOLTAGE Uoc/lcw (1.2/50 ?s, 8/20?s) 10kV/5kA, 1P+N, WITH REMOTE CONTACT

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LOVATO ELECTRIC > Surge protection devices - LOVATO ELECTRIC
--------------	--

Additional Product Information

SA31NA320R

Surge protection device type 3, with plug-in cartridge, combination wave Uoc/lcw (1.2/50 us, 8/20us) 10kV/5kA, 1P+N, with remote contact

Technical specifications

Type of product:SPDType of system:230/400VACType / Class:3Number of poles:1P+NType of mounting:Din railOrder code

SA31NA320R

Weight [g] 140

Qty. per package 1
Multiple qty. of packs per order 1
Package dimensions [mm] 110X075X025
Volume [cm³] 206.25
Bar code [EAN13] 8013975231036
HS Code 85365080
76.17 £
ETIM for SA31NA320R Earthing, lightning and surge protection (EC000942)
Feature Name
Feature Value
Degree of protection (IP) (EF005474)
IP20
Signalling at the device (EF004241)
Optic
Mounting method (EF000003)
DIN rail (top hat rail) 35 mm
With interference suppressor filter (EF006025)
No
Category type 3 (EF004231)
Yes
With remote signalling contact (EF000422)
Yes
Max. overcurrent protection device, series connection (fuse) (EF015963)
10 A
Max. overcurrent protection device, parallel connection (fuse) (EF015962)
10 A
Max. conductor cross section flexible (fine-strand) (EF008828)
4 mm²
Max. conductor cross section solid (solid, stranded) (EF008827)
6 mm²
Voltage protection level L-N (EF004236)
1500 kV
Nominal voltage AC (EF004220)
230 V
Max. continuous voltage AC (EF004198)
320 V
Voltage protection level (EF003525)
1500 kV
Number of poles (EF001391)
2

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / SA31NA320R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.