

INDUSTRIAL COMPONENT DATA

SM1P1800 LOVATO MOTOR PROTECTION CIRCUIT BREAKER, IEC BREAKING CAPACITY ICU 25KA AT 400V, 13...18A

Brand: LOVATO ELECTRIC | Manufacturer Part Number: SM1P1800



Manufacturer	LOVATO ELECTRIC
MPN / Reference	SM1P1800
Catalog number	10000
Category	Motor protection circuit-breaker
Minimum order	1 Pcs
Document ID	EO-BEB295C10B
Generated	2026-08-03

Product Overview

MOTOR PROTECTION CIRCUIT BREAKER, IEC BREAKING CAPACITY ICU 25KA AT 400V, 13...18A

MOTOR PROT.CIRC.BR. SM1P 13-18A

Motor protection circuit breaker, IEC breaking capacity Icu 25kA at 400V, 13...18A

MOTOR PROTECTION SWITCH, ICU INT. POWER AT 400V = 25KA, 13...18A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Motor protection circuit breakers - LOVATO ELECTRIC

Additional Product Information

SM1P1800

Motor protection circuit breaker, IEC breaking capacity Icu 25kA at 400V, 13...18A

Technical specifications

Type of product: Motor protection circuit breaker
Thermal trip adjustment range [A]: 13...18
Rated current In [A]: 18
Short-circuit current breaking capacity (Icu) at AC 400V [kA]: 25
Type of protection: Magnetic and thermal
Type of control: Push button
Certified UL Type E: No
Order code SM1P1800

Weight [g] 300

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 080X047X098

Volume [cm³] 368.48
Bar code [EAN13] 8013975216217
HS Code 85362010
75.71 £
ETIM for SM1P1800 Low-voltage industrial controls and switchgear (EC000074)
Feature Name
Feature Value
Device construction (EF008240)
Complete device in housing
Switch off technique (EF007007)
Thermomagnetic
Type of control element (EF006976)
Push button
Type of electrical connection of main circuit (EF006819)
Screw connection
Degree of protection (IP) (EF005474)
IP20
Adjustment range undelayed short-circuit release (EF007131)
234 A
Overload release current setting (EF002336)
13 A
Rated operating voltage (EF001435)
0 V
Phase failure sensitive (EF007400)
Yes
With thermal overload protection (EF006233)
Yes
With integrated under voltage release (EF001390)
No
With integrated auxiliary switch (EF001387)
No
Rated short-circuit breaking capacity I_{cu} at 400 V, AC (EF007049)
25 kA
Number of poles (EF001391)
3
Rated permanent current I_u (EF001389)
18 A
Depth (EF000049)
75 mm
Height (EF000040)
97 mm
Width (EF000008)....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / SM1P1800 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.