

INDUSTRIAL COMPONENT DATA

51ADX0045B ADX0045B LOVATO SOFT STARTER, ADX TYPE, FOR SEVERE DUTY (STARTING CURRENT 5•IE). WITH INTEGRATED ..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: 51ADX0045B



Manufacturer	LOVATO ELECTRIC
MPN / Reference	51ADX0045B
Catalog number	ADX0045B
Category	Soft starter
Minimum order	1 Pcs
Document ID	EO-67E125FEAD
Generated	2026-08-01

Product Overview

SOFT STARTER, ADX TYPE, FOR SEVERE DUTY (STARTING CURRENT 5•IE). WITH INTEGRATED BY-PASS CONTACTOR, 45A

ADX static starter. B with built-in by-pass (Severe Applications, starting current = 5Ie) 45A

Soft starter, ADX... type, for severe duty (starting current 5•Ie). With integrated by-pass contactor, 45A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Soft Starters / Starters Static - LOVATO ELECTRIC

Additional Product Information

51ADX0045B

Soft starter, ADX... type, for severe duty (starting current 5•Ie). With integrated by-pass contactor, 45A

Technical specifications

Type of product:Advanced, three phase controlNumber of controlled phases:3Rated operational

voltage:208...500VACRated supply voltage:208...240VACRated starter current Ie [A]:45Rated motor power 230VAC

[kW]:11Rated motor power 400VAC [kW]:22Rated motor power 500VAC [KW]:30Functions:Motor current thermal

protection, starting with current limit, torque control, kick start, dynamic braking, PTC input, event log, RS232Order code

51ADX0045B

Weight [g] 9220

Qty. per package 1

Multiple qty. of packs per order 1
Package dimensions [mm] 385X165X240
Volume [cm³] 15246
Bar code [EAN13] 8013975063835
HS Code 85371098
2374.96 £
ETIM for 51ADX0045B Low-voltage industrial controls and switchgear (EC000640)
Feature Name
Feature Value
Voltage type for actuating (EF008242)
DC
Degree of protection (IP) (EF005474)
IP20
Function (EF000030)
Single direction
Rated control supply voltage AC 60 Hz (EF003979)
208 V
Rated control supply voltage AC 50 Hz (EF003978)
208 V
Rated operating voltage U_e (EF002418)
208 V
Torque control (EF009215)
Yes
Internal bypass (EF009214)
Yes
Integrated motor overload protection (EF007297)
Yes
With display (EF000458)
Yes
Rated surrounding temperature without derating (EF007074)
55 °C
Rated power three-phase motor, inline, at 400 V (EF007054)
22 kW
Rated power three-phase motor, inline, at 230 V (EF007053)
11 kW
Rated operation current....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / 51ADX0045B with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.