

## INDUSTRIAL COMPONENT DATA

# 51ADX0470 ADX0470 LOVATO SOFT STARTER, ADX TYPE, FOR SEVERE DUTY (STARTING CURRENT 5•IE). PREDISPOSED FOR EX..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: 51ADX0470



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | LOVATO ELECTRIC |
| MPN / Reference | 51ADX0470       |
| Catalog number  | ADX0470         |
| Category        | Soft starter    |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-977908FFB7   |
| Generated       | 2026-08-03      |

## Product Overview

SOFT STARTER, ADX TYPE, FOR SEVERE DUTY (STARTING CURRENT 5•IE). PREDISPOSED FOR EXTERNAL BY-PASS CONTACTOR, 470A

Start. 470A

Soft starter, ADX... type, for severe duty (starting current 5•Ie). Predisposed for external by-pass contactor, 470A

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Soft Starters / Starters Static - LOVATO ELECTRIC

## Additional Product Information

51ADX0470

Soft starter, ADX... type, for severe duty (starting current 5•Ie). Predisposed for external by-pass contactor, 470A

Technical specifications

Type of product:Advanced, three phase controlNumber of controlled phases:3Rated operational

voltage:208...415VACRated supply voltage:208...240VACRated starter current Ie [A]:470Rated motor power 230VAC

[kW]:132Rated motor power 400VAC [kW]:250Rated motor power 500VAC [kW]:315Functions:Motor current thermal

protection, starting with current limit, torque control, kick start, dynamic braking, PTC input, event log, RS232Order code

51ADX0470

Weight [g] 95000

Qty. per package 1

Multiple qty. of packs per order 1  
Package dimensions [mm] 790X650X430  
Volume [cm<sup>3</sup>] 220805  
Bar code [EAN13] 8013975064139  
HS Code 85371098  
11640.48 £  
ETIM for 51ADX0470 Low-voltage industrial controls and switchgear (EC000640)  
Feature Name  
Feature Value  
Voltage type for actuating (EF008242)  
DC  
Degree of protection (IP) (EF005474)  
IP00  
Function (EF000030)  
Single direction  
Rated control supply voltage AC 60 Hz (EF003979)  
208 V  
Rated control supply voltage AC 50 Hz (EF003978)  
208 V  
Rated operating voltage U<sub>e</sub> (EF002418)  
208 V  
Torque control (EF009215)  
Yes  
Internal bypass (EF009214)  
No  
Integrated motor overload protection (EF007297)  
Yes  
With display (EF000458)  
Yes  
Rated surrounding temperature without derating (EF007074)  
55 °C  
Rated power three-phase motor, inline, at 400 V (EF007054)  
250 kW  
Rated power three-phase motor, inline, at 230 V (EF007053)  
132 kW  
Rated ope...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / 51ADX0470 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.