

INDUSTRIAL COMPONENT DATA

ADXC045400 LOVATO SOFT STARTER, ADXC... TYPE, WITH INTEGRATED BY-PASS RELAY. THREE-PHASE 400VAC MOTOR CONTROL,...

Brand: LOVATO ELECTRIC | Manufacturer Part Number: ADXC045400



Manufacturer	LOVATO ELECTRIC
MPN / Reference	ADXC045400
Catalog number	045400
Category	Soft starter
Minimum order	1 Pcs
Document ID	EO-B225803423
Generated	2026-08-01

Product Overview

SOFT STARTER, ADXC... TYPE, WITH INTEGRATED BY-PASS RELAY. THREE-PHASE 400VAC MOTOR CONTROL, AUXILIARY SUPPLY: STARTER 110...400VAC (L1-L2-L3 INPUTS); START COMMAND 110-400VAC (A1-A2 TERMINALS), 45A

SOFT STARTER 45A 400V

Soft starter, ADXC... type, with integrated by-pass. Three-phase 400VAC motor control, auxiliary supply: starter 110...400VAC (L1-L2-L3 inputs); start command 110-400VAC (A1-A2 terminals), 45A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Soft Starters / Starters Static - LOVATO ELECTRIC

Additional Product Information

ADXC045400

Soft starter, ADXC... type, with integrated by-pass. Three-phase 400VAC motor control, auxiliary supply: starter 110...400VAC (L1-L2-L3 inputs); start command 110-400VAC (A1-A2 terminals), 45A

Technical specifications

Type of product:Ultra compact, two phase controlNumber of controlled phases:2Rated operational

voltage:220...400VACRated supply voltage:110...400VACRated starter current I_e [A]:45Rated motor power 230VAC

[kW]:11Rated motor power 400VAC [kW]:22Functions:Basic parameters onlyOrder code ADXC045400

Weight [g] 760

Qty. per package 1
Multiple qty. of packs per order 1
Package dimensions [mm] 205X175X050
Volume [cm³] 1793.75
Bar code [EAN13] 8013975209547
HS Code 85044090
ETIM for ADXC045400 Low-voltage industrial controls and switchgear (EC000640)
Feature Name
Feature Value
Voltage type for actuating (EF008242)
AC
Degree of protection (IP) (EF005474)
IP20
Function (EF000030)
Single direction
Rated control supply voltage AC 60 Hz (EF003979)
110 V
Rated control supply voltage AC 50 Hz (EF003978)
100 V
Rated operating voltage U_e (EF002418)
220 V
Torque control (EF009215)
No
Internal bypass (EF009214)
Yes
Integrated motor overload protection (EF007297)
No
With display (EF000458)
No
Rated surrounding temperature without derating (EF007074)
60 °C
Rated power three-phase motor, inline, at 400 V (EF007054)
22 kW
Rated power three-phase motor, inline, at 230 V (EF007053)
11 kW
Rated operation current I_e at 40 °C T_u (EF007039)
45 A

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / ADXC045400 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.