

INDUSTRIAL COMPONENT DATA

ADXC02540024 LOVATO SOFT STARTER, ADXC... TYPE, WITH INTEGRATED BY-PASS RELAY. THREE-PHASE 400VAC MOTOR CONTRO..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: ADXC02540024



Manufacturer	LOVATO ELECTRIC
MPN / Reference	ADXC02540024
Catalog number	02540024
Category	Soft starter
Minimum order	1 Pcs
Document ID	EO-24D1113AD7
Generated	2026-08-02

Product Overview

SOFT STARTER, ADXC... TYPE, WITH INTEGRATED BY-PASS RELAY. THREE-PHASE 400VAC MOTOR CONTROL, AUXILIARY SUPPLY: STARTER 110...400VAC (L1-L2-L3 INPUTS); START COMMAND 24VAC/DC (A1-A2 TERMINALS), 25A

SOFT STARTER 25A 400V UC 24VAC/DC

Soft starter, ADXC... type, with integrated by-pass. Three-phase 400VAC motor control, auxiliary supply: starter 110...400VAC (L1-L2-L3 inputs); start command 24VAC/DC (A1-A2 terminals), 25A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Soft Starters / Starters Static - LOVATO ELECTRIC

Additional Product Information

ADXC02540024

Soft starter, ADXC... type, with integrated by-pass. Three-phase 400VAC motor control, auxiliary supply: starter 110...400VAC (L1-L2-L3 inputs); start command 24VAC/DC (A1-A2 terminals), 25A

Technical specifications

Type of product:Ultra compact, two phase controlNumber of controlled phases:2Rated operational voltage:220...400VACRated supply voltage:24VAC/DCRated starter current I_e [A]:25Rated motor power 230VAC [kW]:5.5Rated motor power 400VAC [kW]:11Functions:Basic parameters onlyOrder code ADXC02540024
Weight [g] 500

Qty. per package 1
Multiple qty. of packs per order 1
Package dimensions [mm] 175X150X050
Volume [cm³] 1312.5
Bar code [EAN13] 8013975209462
HS Code 85044090
ETIM for ADXC02540024 Low-voltage industrial controls and switchgear (EC000640)
Feature Name
Feature Value
Voltage type for actuating (EF008242)
AC/DC
Degree of protection (IP) (EF005474)
IP20
Function (EF000030)
Single direction
Rated control supply voltage DC (EF003980)
24 V
Rated control supply voltage AC 60 Hz (EF003979)
110 V
Rated control supply voltage AC 50 Hz (EF003978)
110 V
Rated operating voltage U_e (EF002418)
220 V
Torque control (EF009215)
No
Internal bypass (EF009214)
Yes
Integrated motor overload protection (EF007297)
No
With display (EF000458)
No
Rated surrounding temperature without derating (EF007074)
60 °C
Rated power three-phase motor, inline, at 400 V (EF007054)
11 kW
Rated power three-phase motor, inline, at 230 V (EF007053)
5.5 kW
Rated operation current I_e at 40 °C T...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / ADXC02540024 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.